

EXPLORE E+ 4 STAGGER



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
MANDO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
PANTALLA	Giant RideControl Dash 2 high-angle visibility, full color LCD display
BATERÍA	Giant EnergyPak Smart 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
CARGADOR	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONECTIVIDAD	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	S, M, L, XL
COLORES	Stealth Chome, Mars Dust
CUADRO	Gen 3 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
HORQUILLA	SR Suntour XCM34 Boost DS 100mm travel 15AH4-110 axle
AMORTIGUADOR	n/a
COMPONENTES	
MANILLAR	Giant Connect Riser 31.8x690mm
PUÑOS	Giant Contact
POTENCIA	Giant Contour integrated 16° (S/M:80mm L/XL/XXL 100mm)
TIJA DE SILLÍN	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SILLÍN	Selle Royal Vivo Ergo Moderate Unisex
PEDALES	Anti-slip Platform Pedal
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Cues
CAMBIO TRASERO	Shimano Cues 9-speed
FRENOS	Tektro HD-M280, hydraulic disc, 180mm
PALANCAS DE FRENOS	Tektro HD-M280
CASETTE	Shimano Cues, 11-36T, 9-speed
CADENA	Shimano Linkglide CN-LG500
JGO. PLATOS Y BIELAS	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 46T

RUEDAS	
LLANTAS	Giant GX03V, 622x21 Aluminium
BUJES	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
RADIOS	Stainless steel, e-bike optimized
CUBIERTAS	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready,w/ Reflection Strip
EXTRAS	Aegis Tire Checker
ACCESORIOS	
LUCES	Recon E HL50 StVZO [F] AXA NYX 6-12V E-bike tail light [R]
CANDADO/ANTI-ROBO	ABUS Xplus battery lock
PORTA-EQUIPAJES	MIK rack. System bag & basket compatible
GUARDABARROS/CUBRE-CADENA	Alluminum
LÍMITES	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

Precio: 2.799,00 €

GEOMETRÍA

CUADRO	S	M
Longitud del tubo del sillín (mm)	435	485
Seat Post Insertion Depth (mm)	260	260
Ángulo del tubo del sillín	73,0°	73,0°
Longitud del tubo superior (mm) (mm)	570	590
Longitud del tubo de dirección (mm) (mm)	130	140
Ángulo del tubo de dirección	69,5°	69,5°
Inclinación de la horquilla (mm)	42	42
Distancia entre ejes (mm) (mm)	1112	1121
Longitud de la vaina (mm) (mm)	455	455
Caída del eje de pedalier (mm) (mm)	60	60
Stack (mm) (mm)	609	618
Reach (mm) (mm)	383	401
Altura del suelo al tubo (mm) (mm)	682	676
Ancho del manillar (mm) (mm)	690	690
Longitud de la potencia (mm) (mm)	60	70
Tamaño de ruedas	700C	700C

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.