

EXPLORE E+ 4 STAGGER

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
CONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2 high-angle visibility, full color LCD display
BATTERY	Giant EnergyPak Smart 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, L, XL
COLORS	Stealth Chome, Mars Dust
FRAME	Gen 3 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
FORK	SR Suntour XCM34 Boost DS 100mm travel 15AH4-110 axle
SHOCK	n/a
COMPONENTS	
HANDLEBAR	Giant Connect Riser 31.8x690mm
GRIPS	Giant Contact
STEM	Giant Contour integrated 16° (S/M:80mm L/XL/XXL 100mm)
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Selle Royal Vivo Ergo Moderate Unisex
PEDALS	Anti-slip Platform Pedal
DRIVETRAIN	
SHIFTERS	Shimano Cues
REAR DERAILLEUR	Shimano Cues 9-speed
BRAKES	Tektro HD-M280, hydraulic disc, 180mm
BRAKE LEVERS	Tektro HD-M280
CASSETTE	Shimano Cues, 11-36T, 9-speed
CHAIN	Shimano Linkglide CN-LG500
CRANKSET	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 46T

WHEELS	
RIMS	Giant GX03V, 622x21 Aluminium
HUBS	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
SPOKES	Stainless steel, e-bike optimized
TIRES	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready,w/ Reflection Strip
EXTRAS	Aegis Tire Checker
ACCESSORIES	
LIGHTING	Recon E HL50 StVZO [F] AXA NYX 6-12V E-bike tail light [R]
LOCK	ABUS Xplus battery lock
CARRIER	MIK rack. System bag & basket compatible
FENDER/CHAINGUARD	Alluminum
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	435	485	535	585
Seat Tube Angle	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	570	590	610	630
Head Tube Length (mm)	130	140	155	170
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	42	42	42	42
Wheelbase (mm)	1112	1121	1142	1163
Chain Stay Length (mm)	455	455	455	455
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	609	618	633	648
Reach (mm)	383	401	416	432
Stand Over Height (mm)	682	676	665	844
Handlebar Width (mm)	690	690	690	690
Stem Length (mm)	60	70	80	90
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.