

EXPLORE E+ 4 STAGGER



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
COMANDO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2 high-angle visibility, full color LCD display
BATTERIA	Giant EnergyPak Smart 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
CARICATORE	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNETTIVITÀ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Stealth Chome
TELAIO	Gen 3 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
FORCELLA	SR Suntour XCM34 Boost DS 100mm travel 15AH4-110 axle
AMMORTIZZATORE	n/a
COMPONENTISTICA	
MANUBRIO	Giant Connect Riser 31.8x690mm
MANOPOLE	Giant Contact
ATTACCO MANUBRIO	Giant Contour integrated 16° (S/M:80mm L/XL/XXL 100mm)
REGGISSELLA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELLA	Selle Royal Vivo Ergo Moderate Unisex
PEDALI	Anti-slip Platform Pedal
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Cues
DERAGLIATORE POSTERIORE	Shimano Cues 9-speed
FRENI	Tektro HD-M280, hydraulic disc, 180mm
COMANDI FRENO	Tektro HD-M280
PACCO PIGNONI	Shimano Cues, 11-36T, 9-speed
CATENA	Shimano Linkglide CN-LG500
GUARNITURA	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 46T

RUOTE	
CERCHI	Giant GX03V, 622x21 Aluminium
MOZZI	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
RAGGI	Stainless steel, e-bike optimized
COPERTONI	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready,w/ Reflection Strip
EXTRA	Aegis Tire Checker
ACCESSORI	
ILLUMINAZIONE	Recon E HL50 StVZO [F] AXA NYX 6-12V E-bike tail light [R]
LUCCHETTO	ABUS Xplus battery lock
PORTAPACCHI	MIK rack. System bag & basket compatible
PARAFANGO / PARACATENA	Alluminum
LIMITI	
LIMITE MASSIMO DI CARICO COMBINATO	Type 3 150kg

Prezzo: 2.999,00 €

GEOMETRIA

TELAIO	S	M	L	XL
Lunghezza Tubo Sella (mm)	435	485	535	585
Profondità inserimento reggisella (mm)	260	260	260	260
Angolo Tubo Sella	73,0°	73,0°	73,0°	73,0°
Lunghezza Tubo Orizzontale (mm)	570	590	610	630
Lunghezza Tubo Sterzo (mm)	130	140	155	170
Angolo Sterzo	69,5°	69,5°	69,5°	69,5°
Rake Forcella (mm)	42	42	42	42
Interasse (mm)	1112	1121	1142	1163
Lunghezza Carro Posteriore (mm)	455	455	455	455
Drop Movimento Centrale (mm)	60	60	60	60
Stack (mm)	609	618	633	648
Reach (mm)	383	401	416	432
Altezza stand over (mm)	682	676	665	844
Larghezza Manubrio c/c (mm)	690	690	690	690
Lunghezza Attacco Manubrio (mm)	60	70	80	90
Dimensione Ruote	700C	700C	700C	700C

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.