

EXPLORE E+ 4 STAGGER

GIANT



SPECS

Tecnologia Híbrida de Ciclismo	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
ECRÃ	Giant RideControl Dash 2 high-angle visibility, full color LCD display
BATERIA	Giant EnergyPak Smart 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
CARREGADOR	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
Quadro	
TAMANHOS	S, M, L, XL
CORES	Stealth Chome, Mars Dust
QUADRO	Gen 3 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
FORQUILHA	SR Suntour XCM34 Boost DS 100mm travel 15AH4-110 axle
AMORTECEDORES	n/a
Componentes	
GUIADOR	Giant Connect Riser 31.8x690mm
PUNHOS	Giant Contact
AVANÇO	Giant Contour integrated 16° (S/M:80mm L/XL/XXL 100mm)
ESPIÃO DE SELIM	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELIM	Selle Royal Vivo Ergo Moderate Unisex
PEDAIS	Anti-slip Platform Pedal
Transmissão	
MANETES	Shimano Cues
DESVIADOR TRASEIRO	Shimano Cues 9-speed
TRAVÕES	Tektro HD-M280, hydraulic disc, 180mm
MANÍPULOS DOS TRAVÕES	Tektro HD-M280
CASSETTE	Shimano Cues, 11-36T, 9-speed
CORRENTE	Shimano Linkglide CN-LG500
CONJUNTO PEDALEIRO	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 46T

Rodas	
AROS	Giant GX03V, 622x21 Aluminium
CUBOS	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
RAIOS	Stainless steel, e-bike optimized
PNEUS	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready,w/ Reflection Strip
EXTRAS	Aegis Tire Checker
Acessórios	
LUZES	Recon E HL50 StVZO [F] AXA NYX 6-12V E-bike tail light [R]
CADEADO	ABUS Xplus battery lock
PORTA-BICICLETAS	MIK rack. System bag & basket compatible
GUARDA LAMAS/PROTECTOR DE CORRENTE	Alluminum
Limites	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

Preço: 2 499,00 €

GEOMETRIA

Quadro	S	M
Comprimento do tubo do assento (mm)	435	485
Seat Post Insertion Depth (mm)	260	260
Ângulo do tubo do assento	73,0°	73,0°
Comprimento do tubo superior (mm)	570	590
Comprimento do tubo principal (mm)	130	140
Ângulo do tubo principal	69,5°	69,5°
Garfo ancinho (mm)	42	42
distância entre eixos (mm)	1112	1121
Comprimento Chain Stay (mm)	455	455
Suporte inferior (mm)	60	60
Pilha (mm)	609	618
Alcançar (mm)	383	401
Altura do standover (mm)	682	676
Largura do guidão (mm)	690	690
Comprimento da haste (mm)	60	70
Tamanho da roda	700C	700C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.