

# EXPLORE E+ 4 STAGGER

GIANT



## SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
TIPALO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
PRIKAZOVALNIK	Giant RideControl Dash 2 high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak Smart 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Stealth Chome, Mars Dust
OKVIR	Gen 3 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VILICE	SR Suntour XCM34 Boost DS 100mm travel 15AH4-110 axle
AMORTIZER	n/a
KOMPONENTE	
KRMILO	Giant Connect Riser 31.8x690mm
GRIPS	Giant Contact
OPORA KRMILA	Giant Contour integrated 16° (S/M:80mm L/XL/XXL 100mm)
OPORA SEDEŽA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDEŽ	Selle Royal Vivo Ergo Moderate Unisex
PEDALA	Anti-slip Platform Pedal
POGON	
PRESTAVNE ROČICE	Shimano Cues
ZADNJI MENJALNIK	Shimano Cues 9-speed
ZAVORE	Tektro HD-M280, hydraulic disc, 180mm
ZAVORNE ROČICE	Tektro HD-M280
VERIŽNIK	Shimano Cues, 11-36T, 9-speed
VERIGA	Shimano Linkglide CN-LG500
GONILKE Z VERIŽNIKI	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 46T

OBROČNIKI	
OBROČI	Giant GX03V, 622x21 Aluminium
PESTA	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
NAPERE	Stainless steel, e-bike optimized
PLAŠČI	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready,w/ Reflection Strip
DODATKI	Aegis Tire Checker
DODATNA OPREMA	
SVETILA	Recon E HL50 StVZO [F] AXA NYX 6-12V E-bike tail light [R]
KLJUČAVNICA	ABUS Xplus battery lock
PRTLJAŽNIK	MIK rack. System bag & basket compatible
BLATNIKI/ŠČITNIK VERIGE	Alluminium
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

## GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	435	485	535	585
Kot sedežne cevi	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	570	590	610	630
Višina glave okvirja (mm)	130	140	155	170
Krmlini kot	69,5°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	42	42	42	42
Medosna razdalja (mm)	1112	1121	1142	1163
Dolžina cevi ob verigi (mm)	455	455	455	455
Bottom Bracket Drop (mm)	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	609	618	633	648
Doseg (mm)	383	401	416	432
Višina zgornje cevi (mm)	682	676	665	844
Širina krmila (mm)	690	690	690	690
Dolžina opore krmila (mm)	60	70	80	90
Velikost obročnikov	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.