

EXPLORE E+ LTD STAGGER



SPECS

HYBRID SYKKEL TEKNOLOGI	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2 high-angle visibility, full color LCD display
BATTERI	iant EnergyPak Smart 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RAMME	
STØRRELSE	S, M, L, XL
FARGE	Stealth Chome, Mars Dust
RAMME	Gen 3 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
GAFFEL	SR Suntour XCM34 Boost DS 100mm travel 15AH4-110 axle
DEMPER	n/a
KOMPONENTER	
STYRE	Giant Connect Riser 31.8x690mm
GRIPS	Giant Contact
STYRSTEM	Giant Contour integrated 16° (S/M:80mm L/XL/XXL 100mm)
SETEPINNE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALER	Anti-slip Platform Pedal
DRIVVERK	
GIRHENDLER	Shimano Cues
BAKGIR	Shimano Cues 9-speed
BREMSER	Tektro HD-M280, hydraulic disc, 180mm
BREMSEHENDLER	Tektro HD-M280
KASSETT	Shimano Cues, 11-36T, 9-speed
KJEDE	Shimano Linkglide CN-LG500
KRANK	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 46T

HJUL	
FELG	Giant GX03V, 622x21 Aluminium
NAV	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
EIKE	Stainless steel, e-bike optimized
DEKK	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready,w/ Reflection Strip
EXTRAS	Aegis Tire Checker
TILBEHØR	
LYS	Recon E HL50 StVZO [F] AXA NYX 6-12V E-bike tail light [R]
LÅS	ABUS Xplus battery lock
BAGASJEBRETT	MIK rack. System bag & basket compatible
SKJERMER/KJEDEBESKYTTER	Alluminum
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

GEOMETRI

RAMME	S	M	L	XL
Seat Tube Length (mm)	435	485	535	585
Seat Post Insertion Depth (mm)	260	260	260	260
Seat Tube Angle	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	570	590	610	630
Head Tube Length (mm)	130	140	155	170
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork rake (mm)	42	42	42	42
Wheelbase (mm)	1112	1121	1142	1163
Chain Stay Length (mm)	455	455	455	455
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	609	618	633	648
Reach (mm)	383	401	416	432
Stand Over Height (mm)	682	676	665	844
Handlebar Width (mm)	690	690	690	690
Stem Length (mm)	60	70	80	90
Wheel Size	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.