

EXPLORE E+ PRO 0 STA



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	Giant SyncDrive Pro 2 85Nm, powered by Yamaha, PedalPlus 6-Sensor technology
OHJAUSYSIKKÖ	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
NÄYTTÖ	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
AKKU	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604)
LATURI	Giant EnergyPak 6A smart charger, 60% charge in 3:00h
YHTEYDET MUIHIN LAITTEISIIN	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RUNKO	
KOOT	S, M, L, XL
VÄRIT	Gunmetal Black
RUNKO	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
HAARUKKA	SR Suntour XCR34 Air Boost, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
KOMONENTIT	
OHJAUSTANKO	Giant Contour Comfort Riser 31.8x690mm
GRIPIT	Giant Connect Ergo Max Cork w/bar-end
OHJAINKANNATIN	Giant Contour EVO integrated 16° (S/M:80mm L/XL/XXL 100mm)
SATULATOLPPA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATULA	Selle Royal Vivo Ergo Moderate Unisex
POLKIMET	Aluminum Platform
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Deore XT, LinkGlide
TAKAVAIHTAJA	Shimano Deore XT, LinkGlide, 11-speed, Shadow+
JARRUT	Shimano XT, hydraulic disc, 203mm
JARRUKAHVAT	Shimano XT
RATASPAKKA	Shimano LinkGlide, CS-LG700-11 11-50T, 11-speed
KETJUT	Shimano CN-LG500
KAMPISARJA	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
KESKIÖ	N/A

RENKAAT	
VANTEET	eX25, Tubeless Ready, 622x25 Aluminium
NAVAT	Giant eTracker, [F] 110x15 [R] 148x12
PINNAT	Stainless steel, e-bike optimized
RENKAAT	Crosscut Gravel 1, 700x57c, Foldable, Tubeless Ready
LISÄTIEDOT	KSA40 direct mount kickstand
TARVIKKEET	
VALOT	Recon E HL100 StVZO [F] AXA NYX 6-12V E-bike tail light with brake sensor [R]
LUKKO	ABUS Xplus battery lock
TAVARATELINE	MIK HD rack. System bag & basket compatible
KETJUNSUOJA	Aluminum Fenders

Suositusinta: 5 389,00 €

GEOMETRIA

RUNKO	S	M
Satulaputken pituus (mm)	410	435
Satulaputken kulma	74,0°	73,5°
Vaakaputken pituus (mm)	585	600
Emäputken pituus (mm)	140	155
Emäputken kulma	69,0°	69,5°
Haarukan offset (mm)	51	51
Trail-mitta (mm)	88	84
Akseliväli (mm)	1147	1151
Takahaarukan alaputken pituus (mm)	455	470
Keskiön pudotus (mm)	60	60
Stack-mitta (mm)	665	682
Reach-mitta (mm)	394	398
Standover-mitta (mm)	682	670
Ohjaustangon leveys (mm)	690	690
Ohjainkannattimen pituus (mm)	60	80
Kammen pituus (mm)	170	170
Rengaskoko	29"	29"

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.