



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro 2 85Nm, powered by Yamaha, PedalPlus 6-Sensor technology
TIPALO	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
PRIKAZOVALNIK	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATERIJA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604)
CHARGER	Giant EnergyPak 6A smart charger, 60% charge in 3:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Gunmetal Black
OKVIR	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VILICE	SR Suntour XCR34 Air Boost, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
KOMPONENTE	
KRMILO	Giant Contour Comfort Riser 31.8x690mm
GRIPS	Giant Connect Ergo Max Cork w/bar-end
OPORA KRMILA	Giant Contour EVO integrated 16° (S/M:80mm L/XL/XXL 100mm)
OPORA SEDEŽA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDEŽ	Selle Royal Vivo Ergo Moderate Unisex
PEDALA	Aluminum Platform
POGON	
PRESTAVNE ROČICE	Shimano Deore XT, LinkGlide
ZADNJI MENJALNIK	Shimano Deore XT, LinkGlide, 11-speed, Shadow+
ZAVORE	Shimano XT, hydraulic disc, 203mm
ZAVORNE ROČICE	Shimano XT
VERIŽNIK	Shimano LinkGlide, CS-LG700-11 11-50T, 11-speed
VERIGA	Shimano CN-LG500
GONILKE Z VERIŽNIKI	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
BOTTOM BRACKET	N/A

OBROČNIKI	
OBROČI	eX25, Tubeless Ready, 622x25 Aluminium
PESTA	Giant eTracker, [F] 110x15 [R] 148x12
NAPERE	Stainless steel, e-bike optimized
PLAŠČI	Crosscut Gravel 1, 700x57c, Foldable, Tubeless Ready
DODATKI	KSA40 direct mount kickstand
DODATNA OPREMA	
SVETILA	Recon E HL100 StVZO [F] AXA NYX 6-12V E-bike tail light with brake sensor [R]
KLJUČAVNICA	ABUS Xplus battery lock
PRTLJAŽNIK	MIK HD rack. System bag & basket compatible
BLATNIKI/ŠČITNIK VERIGE	Aluminum Fenders

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	410	435	490	545
Kot sedežne cevi	74,0°	73,5°	73,0°	73,0°
Top Tube Length (mm)	585	600	610	630
Višina glave okvirja (mm)	140	155	170	185
Krmilni kot	69,0°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	51	51	51	51
Trail (mm)	88	84	84	84
Medosna razdalja (mm)	1147	1151	1156	1177
Dolžina cevi ob verigi (mm)	455	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	665	682	696	710
Doseg (mm)	394	398	397	413
Višina zgornje cevi (mm)	682	670	650	649
Širina krmila (mm)	690	690	690	690
Dolžina opore krmila (mm)	60	80	100	100
Dolžina gonilke (mm)	170	170	170	170
Velikost obročnikov	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.