

EXPLORE E+ PRO 0 STA



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Pro 2 85Nm, powered by Yamaha, PedalPlus 6-Sensor technology
KONTROLLER	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
VISA	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERI	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604)
LADDARE	Giant EnergyPak 6A smart charger, 60% charge in 3:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Gunmetal Black
RAM	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
GAFFEL	SR Suntour XCR34 Air Boost, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
KOMPONENTER	
STYRE	Giant Contour Comfort Riser 31.8x690mm
GREPPAR	Giant Connect Ergo Max Cork w/bar-end
STAM	Giant Contour EVO integrated 16° (S/M:80mm L/XL/XXL 100mm)
SADELSTOLPE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALER	Aluminum Platform
DRIVLINA	
VÄXLAR	Shimano Deore XT, LinkGlide
BAKVÄXEL	Shimano Deore XT, LinkGlide, 11-speed, Shadow+
BROMSAR	Shimano XT, hydraulic disc, 203mm
BROMSSPAKAR	Shimano XT
KASSETT	Shimano LinkGlide, CS-LG700-11 11-50T, 11-speed
KEDJA	Shimano CN-LG500
VEVPARTI	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
BROMSREGLAGE	N/A

HJUL	
FÄLGAR	eX25, Tubeless Ready, 622x25 Aluminium
NAV	Giant eTracker, [F] 110x15 [R] 148x12
EKRAR	Stainless steel, e-bike optimized
DÄCK	Crosscut Gravel 1, 700x57c, Foldable, Tubeless Ready
EXTRAFUNKTIONER	KSA40 direct mount kickstand
TILLBEHÖR	
BELYSNING	Recon E HL100 StVZO [F] AXA NYX 6-12V E-bike tail light with brake sensor [R]
LÄSA	ABUS Xplus battery lock
BÄRARE	MIK HD rack. System bag & basket compatible
STÄNKSKÄRM/KEDJESKYDD	Aluminum Fenders

Price: 61 190,00 kr

GEOMETRY

RAM	S	M
Längd sadelrör (mm)	410	435
Vinkel sadelrör	74,0°	73,5°
Topprörets längd (mm)	585	600
Styrhuvud Längd (mm)	140	155
Vinkel styrhuvud	69,0°	69,5°
Gaffelvinkel (mm)	51	51
Spår (mm)	88	84
Hjulbas (mm)	1147	1151
Kedjestagslängd (mm)	455	470
Nedre fäste Drop (mm)	60	60
Stack (mm)	665	682
Reach (mm)	394	398
Stå över höjden (mm)	682	670
Styrets bredd (mm)	690	690
Stamlängd (mm)	60	80
Vevlängd (mm)	170	170
Hjulstorlek	29"	29"

All specifications listed are subject to change without notice.