

EXPLORE E+ PRO 0 STAGGER

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 2 85Nm, powered by Yamaha, PedalPlus 6-Sensor technology
BEDIENINGSUNIT	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
ACCU	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604)
LADER	Giant EnergyPak 6A smart charger, 60% charge in 3:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	S, M, L, XL
KLEUREN	Gunmetal Black
FRAME	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VOORVORK	SR Suntour XCR34 Air Boost, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
ONDERDELEN	
STUUR	Giant Contour Comfort Riser 31.8x690mm
HANDVATTEN	Giant Connect Ergo Max Cork w/bar-end
STUURPEN	Giant Contour EVO integrated 16° (S/M:80mm L/XL/XXL 100mm)
ZADEL	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
ZADEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALEN	Aluminum Platform
AFMONTAGE	
SHIFTERS	Shimano Deore XT, LinkGlide
ACHTERDERAILLEUR	Shimano Deore XT, LinkGlide, 11-speed, Shadow+
REMMEN	Shimano XT, hydraulic disc, 203mm
REMHENDELS	Shimano XT
CASSETTE	Shimano LinkGlide, CS-LG700-11 11-50T, 11-speed
AANDRIJVING	Shimano CN-LG500
CRANKSET	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
BOTTOM BRACKET	N/A

WIELSET	
VELGEN	eX25, Tubeless Ready, 622x25 Aluminium
NAVEN	Giant eTracker, [F] 110x15 [R] 148x12
SPAKEN	Stainless steel, e-bike optimized
BANDEN	Crosscut Gravel 1, 700x57c, Foldable, Tubeless Ready
EXTRA'S	KSA40 direct mount kickstand
ACCESSOIRES	
VERLICHTING	Recon E HL100 StVZO [F] AXA NYX 6-12V E-bike tail light with brake sensor [R]
SLOT	ABUS Xplus battery lock
DRAGER	MIK HD rack. System bag & basket compatible
SPATBORD/ KETTINGKAST	Aluminum Fenders

Adviesprijs: € 5.199,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis Lengte (mm)	410	435	490	545
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	585	600	610	630
Balhoofdbuis Lengte (mm)	140	155	170	185
Balhoofdbuis Hoek	69,0°	69,5°	69,5°	69,5°
Vork Sprong (mm)	51	51	51	51
Naloop (mm)	88	84	84	84
Wielbasis (mm)	1147	1151	1156	1177
Liggende achtervork lengte (mm)	455	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	665	682	696	710
Reach (mm)	394	398	397	413
Stand Over Height (mm)	682	670	650	649
Stuur breedte (mm)	690	690	690	690
Stuurpen Lengte (mm)	60	80	100	100
Cranklengte (mm)	170	170	170	170
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.