

EXPRESSION E+ 1

GIANT



SPECIFIKATIONER

HYBRID CYCLING TECHNOLOGY

MOTOR	Giant SyncDrive Core, 50Nm, Powered by Yamaha, PedalPlus 6-sensor technology
KONTROLLER	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
DISPLAY	Giant RideControl Dash, high-angle visibility, full color LCD display
BATTERI	Personal battery choice: 500Wh or 600Wh (suggested retail price based on 500Wh), CO2 neutral production

RAMME

STØRRELSER	S, M, L
FARVER	Thruffle, Amber Glow
RAMME	ALUX aluminium, monotube extra low-stepthrough design.
FORGAFFEL	SR Suntour NEX E25 DS Coil, 63mm travel

KOMPONENTER

STYR	Alluminium, 30° back sweep, 31.8x660 mm
GREB / STYRBÅND	Comfort Ergo Microtech Plus
FREMPIND	Aluminum angle adjustable stem
SADELPIND	Suspension 30.9x300mm
SADEL	Selle Royal Essenza Plus
PEDALER	Wellgo C097, PP/ Kraton body, Anti-slip

GEARGRUPPE

SKIFTEGREB	Shimano Nexus 8-speed RevoShift
BREMSE	Shimano BR-MT200 hydraulic disc, 180mm [F], 160mm [R]
BREMSEGREB	Shimano BL-MT200
KASSETTE	18T
KÆDE	KMC Z1e HX, e-bike optimized
KRANKSÆT	Aluminum 38T

HJUL

FÆLGE	Giant Double Wall Aluminum 622x21
NAV	Shimano HB-TC500-15 100x15 [F], Shimano Nexus 8 disc brake [R]
EGER	Stainless 14G(2.0mm) [F]Stainless 13-14G(2.3-2.0mm) butted [R]
DÆK	CST Xpedium One 45x622 w/ reflective stripe
TILBEHØR	
LYGTER	Axa Blueline 30 LED [F]Axa Blue Line Steady E6 [R]
LÅS	ABUS Pro Shield 5850 (w/o chip) LH KR OEM
BAGAGEBÆRER	MIK rack. System bag & basket compatible

Pris: 20.999,00 kr.

GEOMETRI

RAMME	S	M	L
Sadelrørslængde (mm)	450	500	550
Sadelrørsinkel	73,0°	72,0°	71,0°
Overrørslængde (mm)	580	595	620
Kronrørslængde (mm)	140	160	180
Kronrørsinkel	70,0°	70,0°	70,0°
Forgaffel fremspring (rake) (mm)	44	44	44
Sti (mm)	88	88	88
Akselafstand (mm)	1107	1111	1124
Kædestagslængde (mm)	470	470	470
Krankboks drop (mm)	60	60	60
Stack (mm)	622	641	659
Reach (mm)	390	387	393
Skridthøjde (mm)	515	515	515
Styrbredde (mm)	690	690	690
Frempindslængde (mm)	90	90	110
Pedalarmslængde (mm)	170	170	170
Hjulstørrelse	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.