



## СПЕЦИФИКАЦИИ

РАМКА	
ЦВЯТ	Raw Aluminum
РАМКА	ALUXX SL-Grade Aluminum front and rear triangles, 12x148mm thru-axle, 130mm FlexPoint suspension
ВИЛКА	Crest TR Elite Lite, FloTune Lite Damper, 140mm
ЗАДЕН АМОРТИСЬОР	Crest FloTrac Lite, 165/45mm, trunion mount
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact TR, 20mm rise, AL6061 aluminum, 680mm
ГРИПОВЕ	Giant small-hand
ЛАПА	Giant Contact, 8 degrees, 40mm
КОЛЧЕ ЗА СЕДАЛКА	Contact Switch AT Lite, 100mm
СЕДАЛКА	Selle Royal Vivo Jr
ПЕДАЛИ	Giant Pinner Lite
DRIVETRAIN	
КОМАНДИ	MicroSHIFT Advent X Trail trigger shifter SL-M9505-R (with nanowire)
ПРЕДЕН ДЕРАЙЛЪОР	N/A
ЗАДЕН ДЕРАЙЛЪОР	Microshift Advent X RD-M6205AM
СПИРАЧКИ	Tektro [F]180mm, [R]160mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Tektro HD-J285
КАСЕТА	Microshift Advent X G-Series 10-speed, 11x48
ВЕРИГА	KMC X10 with missing link
КУРБЕЛ	ProWheel Charm, 30t, 140mm
СРЕДНА КАСЕТА	Press Fit

КАПЛИ	
ШИНИ	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology [F] 24" [R] 24"
ГЛАВИНИ	[F] Giant alloy, DBL, six-bolt [R] TRA HE, DBL, 72t pawl driver, 6 bolt
СПИЦИ	Sapim Laser
ГУМИ	[F] Maxxis Minion DHF, 24x2.5, 60 TPI, folding, [R] Maxxis Minion DHR II, 24x2.4, 60 TPI, folding
ЕКСТРИ	Giant 1x chain guide

## ГЕОМЕТРИЯ

РАМКА	One Size
Seat Tube Length (mm)	320
Seat Tube Angle	77,0°
Top Tube Length (mm)	500
Head Tube Length (mm)	105
Head Tube Angle	64,5°
Fork Rake (mm)	30
Trail (mm)	119,2
Wheelbase (mm)	1054,1
Chain Stay Length (mm)	390
Bottom Bracket Drop (mm)	
Stack (mm)	534,6
Обсер (mm)	376,6
Stand Over Height (mm)	641
Ширина на Кормило (mm)	680
Дължина на Лапа (mm)	40
Дължина на Курбел (mm)	140
Размер на Каплите	24"

All specifications listed are subject to change without notice.