



SPECS

FRAME	
COLORS	Raw Aluminum
FRAME	ALUXX SL-Grade Aluminum front and rear triangles, 12x148mm thru-axle, 130mm FlexPoint suspension
FORK	Crest TR Elite Lite, FloTune Lite Damper, 140mm
SHOCK	Crest FloTrac Lite, 165/45mm, trunnion mount
COMPONENTS	
HANDLEBAR	Giant Contact TR, 20mm rise, AL6061 aluminum, 680mm
GRIPS	Giant small-hand
STEM	Giant Contact, 8 degrees, 40mm
SEATPOST	Contact Switch AT Lite, 100mm
SADDLE	Selle Royal Vivo Jr
PEDALS	Giant Pinner Lite
DRIVETRAIN	
SHIFTERS	MicroSHIFT Advent X Trail trigger shifter SL-M9505-R (with nanowire)
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Microshift Advent X RD-M6205AM
BRAKES	Tektro [F]180mm, [R]160mm
BRAKE LEVERS	Tektro HD-J285
CASSETTE	Microshift Advent X G-Series 10-speed, 11x48
CHAIN	KMC X10 with missing link
CRANKSET	ProWheel Charm, 30t, 140mm
BOTTOM BRACKET	Press Fit

WHEELS	
RIMS	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology [F] 24" [R] 24"
HUBS	[F] Giant alloy, DBL, six-bolt [R] TRA HE, DBL, 72t pawl driver, 6 bolt
SPOKES	Sapim Laser
TIRES	[F] Maxxis Minion DHF, 24x2.5, 60 TPI, folding, [R] Maxxis Minion DHR II, 24x2.4, 60 TPI, folding
EXTRAS	Giant 1x chain guide

GEOMETRY

FRAME	One Size
Seat Tube Length (mm)	320
Seat Tube Angle	77.0°
Top Tube Length (mm)	500
Head Tube Length (mm)	105
Head Tube Angle	64.5°
Fork Rake (mm)	30
Trail (mm)	119.2
Wheelbase (mm)	1054.1
Chain Stay Length (mm)	390
Bottom Bracket Drop (mm)	
Stack (mm)	534.6
Reach (mm)	376.6
Stand Over Height (mm)	641
Handlebar Width (mm)	680
Stem Length (mm)	40
Crank Length (mm)	140
Wheel Size	24"

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.