



SPECIFIKACIJE

OKVIR	
BOJE	Raw Aluminum
OKVIR	ALUXX SL-Grade Aluminum front and rear triangles, 12x148mm thru-axle, 130mm FlexPoint suspension
VILICA	Crest TR Elite Lite, FloTune Lite Damper, 140mm
AMORTIZER	Crest FloTrac Lite, 165/45mm, trunnion mount
KOMPONENTE	
VOLAN	Giant Contact TR, 20mm rise, AL6061 aluminum, 680mm
GRIPS	Giant small-hand
LULA VOLANA	Giant Contact, 8 degrees, 40mm
CIJEV SJEDALA	Contact Switch AT Lite, 100mm
SJEDALO	Selle Royal Vivo Jr
PEDALE	Giant Pinner Lite
POGON	
RUČICE MJENJAČA	MicroSHIFT Advent X Trail trigger shifter SL-M9505-R (with nanowire)
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	Microshift Advent X RD-M6205AM
KOČNICE	Tektro [F]180mm, [R]160mm
RUČICE KOČNICA	Tektro HD-J285
KAZETA	Microshift Advent X G-Series 10-speed, 11x48
LANAC	KMC X10 with missing link
POGON	ProWheel Charm, 30t, 140mm
OSOVINA POGONA (BB)	Press Fit

KOTAČI	
OBRUČI	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology [F] 24" [R] 24"
NABE	[F] Giant alloy, DBL, six-bolt [R] TRA HE, DBL, 72t pawl driver, 6 bolt
ŽBICE	Sapim Laser
GUME	[F] Maxxis Minion DHF, 24x2.5, 60 TPI, folding, [R] Maxxis Minion DHR II, 24x2.4, 60 TPI, folding
DODACI	Giant 1x chain guide

GEOMETRIJA

OKVIR	One Size
Dužina cijevi sjedala (mm)	320
Kut cijevi sjedala	77,0°
Dužina gornje cijevi (mm)	500
Dužina prednje cijevi (mm)	105
Kut vilice	64,5°
Zakrivljenost vilice (offset) (mm)	30
Staza (mm)	119,2
Međuosovinski razmak kotača (mm)	1054,1
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	390
Položaj osovine pogona (mm)	
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	534,6
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	376,6
Prekoračna visina (mm)	641
Širina volana (mm)	680
Dužina lule volana (mm)	40
Dužina poluge pedale (mm)	140
Veličina kotača	24"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.