



SPECS

QUADRO	
CORES	Raw Aluminum
QUADRO	ALUXX SL-Grade Aluminum front and rear triangles, 12x148mm thru-axle, 130mm FlexPoint suspension
FORQUILHA	Crest TR Elite Lite, FloTune Lite Damper, 140mm
AMORTECEDORES	Crest FloTrac Lite, 165/45mm, trunnion mount
COMPONENTES	
GUIADOR	Giant Contact TR, 20mm rise, AL6061 aluminum, 680mm
PUNHOS	Giant small-hand
AVANÇO	Giant Contact, 8 degrees, 40mm
ESPIGÃO DE SELIM	Contact Switch AT Lite, 100mm
SELIM	Selle Royal Vivo Jr
PEDAIS	Giant Pinner Lite
TRANSMISSÃO	
MANETES	MicroSHIFT Advent X Trail trigger shifter SL-M9505-R (with nanowire)
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	Microshift Advent X RD-M6205AM
TRAVÕES	Tektro [F]180mm, [R]160mm
MANÍPULOS DOS TRAVÕES	Tektro HD-J285
CASSETE	Microshift Advent X G-Series 10-speed, 11x48
CORRENTE	KMC X10 with missing link
CONJUNTO PEDALEIRO	ProWheel Charm, 30t, 140mm
MOVIMENTO CENTRAL	Press Fit

RODAS	
AROS	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology [F] 24" [R] 24"
CUBOS	[F] Giant alloy, DBL, six-bolt [R] TRA HE, DBL, 72t pawl driver, 6 bolt
RAIOS	Sapim Laser
PNEUS	[F] Maxxis Minion DHF, 24x2.5, 60 TPI, folding, [R] Maxxis Minion DHR II, 24x2.4, 60 TPI, folding
EXTRAS	Giant 1x chain guide

Preço: 2 099,00 €

GEOMETRIA

QUADRO	One Size
Comprimento do tubo do assento (mm)	320
Ângulo do tubo do assento	77,0°
Comprimento do tubo superior (mm)	500
Comprimento do tubo principal (mm)	105
Ângulo do tubo principal	64,5°
Garfo ancinho (mm)	30
Trilha (mm)	119,2
distância entre eixos (mm)	1054,1
Comprimento Chain Stay (mm)	390
Suporte inferior (mm)	
Pilha (mm)	534,6
Alcançar (mm)	376,6
Altura do standover (mm)	641
Largura do guidão (mm)	680
Comprimento da haste (mm)	40
Comprimento da Manivela (mm)	140
Tamanho da roda	24"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.