



SPECS

QUADRO	
TAMANHOS	OSFM
CORES	Cyber Lime
QUADRO	ALUXX SL-grade aluminum front and rear triangles, 130mm FlexPoint suspension, 24-inch rear wheel compatible
FORQUILHA	Giant CREST TR, 140mm, FLOTUNE damper, 24-inch wheel compatible, custom "light weight" tune
AMORTECEDORES	Giant CREST FLOTRAC Lite, 165/45, trunnion mount, custom "light weight" tune
COMPONENTES	
GUIADOR	Giant Connect TR, alloy, 740mm, 20mm rise
PUNHOS	Giant, custom small-hand sizing
AVANÇO	Giant Contact, 8-degree, 40mm
ESPIÃO DE SELIM	Contact Switch AT Lite dropper, remote, 100mm travel, 30.9mm
SELIM	Selle Royal Vivo Jr.
TRANSMISSÃO	
MANETES	MicroSHIFT Advent X, 1x10
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	MicroSHIFT Advent X
TRAVÕES	Tektro HD-J2820, hydraulic, Tektro rotors [F]180mm, [R]160mm
MANÍPULOS DOS TRAVÕES	Tektro HD-J2820
CASSETTE	MicroSHIFT Advent X, G-Series, 11x48
CORRENTE	KMC X10
CONJUNTO PEDALEIRO	ProWheel CHARM, 30t, 140m
MOVIMENTO CENTRAL	Press Fit

RODAS	
AROS	Giant TRA WheelSystem, aluminum, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology, [F] 24-inch, [R] 24-inch
CUBOS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), 6-bolt, MicroDrive driver body
RAIOS	Sapim, 28, straight pull, DBL Technology
PNEUS	[F] Maxxis Minion DHF, 24x2.4, 60 tpi [R] Maxxis Minion DHR II, 24x2.3, 60 tpi
EXTRAS	Giant 1x chain guide

Preço: 2 149,00 €

GEOMETRIA

QUADRO	One Size
Comprimento do tubo do assento (mm)	320
Seat Post Insertion Depth (mm)	258
Ângulo do tubo do assento	77,0°
Comprimento do tubo superior (mm)	500
Comprimento do tubo principal (mm)	105
Ângulo do tubo principal	64,5°
Garfo ancinho (mm)	30
Trilha (mm)	119,2
distância entre eixos (mm)	1054
Comprimento Chain Stay (mm)	390
Suporte inferior (mm)	
Pilha (mm)	535
Alcançar (mm)	377
Altura do standover (mm)	641
Largura do guidão (mm)	680
Comprimento da haste (mm)	40
Comprimento da Manivela (mm)	140

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.