FAITH 24 SE



產品規格

車架	
車架	ALUXX SL-grade aluminum front and rear triangles, 130mm FlexPoint suspension, 24-inch rear wheel compatible
前叉	Giant CREST TR, 140mm, FLOTUNE damper, 24-inch wheel compatible, custom "light weight" tune
避震器	Giant CREST FLOTRAC Lite, 165/45, trunnion mount, custom "light weight" tune
COMPONENTS	
車把手	Giant Connect TR, alloy, 740mm, 20mm rise
把手帶/套	Giant, custom small-hand sizing
豎桿	Giant Contact, 8-degree, 40mm
座桿	Contact Switch AT Lite dropper, remote, 100mm travel, 30.9mm
坐墊	Selle Royal Vivo Jr.
DRIVETRAIN	
變速把手	MicroSHIFT Advent X, 1x10
後變速器	MicroSHIFT Advent X
煞車系統	Tektro HD-J2820, hydraulic, Tektro rotors [F]180mm, [R]160mm
煞車把手	Tektro HD-J2820
飛輪	MicroSHIFT Advent X, G-Series, 11x48
鍊條	KMC X10
大齒盤	ProWheel CHARM, 30t, 140m
BOTTOM BRACKET (B B)	Press Fit

輪組	
輪圈	Giant TRA WheelSystem, aluminum, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology, [F] 24-inch, [R] 24-inch
花鼓	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), 6-bolt, MicroDrive driver body
輻條	Sapim, 28, straight pull, DBL Technology
外胎	[F] Maxxis Minion DHF, 24x2.4, 60 tpi [R] Maxxis Minion DHR II, 24x2.3, 60 tpi
ACCESSORIES	
FENDER/CHAINGUARD	Giant 1x chain guide

Price: NT$59,800

車架幾何

車架	One Size
座(立)管長 (mm)	320
Seat Post Insertion Depth (mm)	258
座(立)管角度	77.0°
上管長度 (mm)	500
頭管長度 (mm)	105
頭管角度	64.5°
前叉 (mm)	30
Trail (mm)	119.2
前後輪距 (mm)	1054
後下叉長度 (mm)	390
五通下降高度 (mm)	
頭碗至五通高度 (mm)	535
頭碗至五通長度 (mm)	377
上管至地面高度 (mm)	641
把手寬 (mm)	680
龍頭長度 (mm)	40
曲柄長度 (mm)	140

捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。