



## SPECIFIKACIJE

OKVIR	
BARVE	Raw Aluminum
OKVIR	ALUXX SL-Grade Aluminum front and rear triangles, 12x148mm thru-axle, 130mm FlexPoint suspension
VILICE	Crest TR Elite Lite, FloTune Lite Damper, 140mm
AMORTIZER	Crest FloTrac Lite, 165/45mm, trunion mount
KOMPONENTE	
KRMILO	Giant Contact TR, 20mm rise, AL6061 aluminum, 680mm
GRIPS	Giant small-hand
OPORA KRMILA	Giant Contact, 8 degrees, 40mm
OPORA SEDEŽA	Contact Switch AT Lite, 100mm
SEDEŽ	Selle Royal Vivo Jr
PEDALA	Giant Pinner Lite
POGON	
PRESTAVNE ROČICE	MicroSHIFT Advent X Trail trigger shifter SL-M9505-R (with nanowire)
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Microshift Advent X RD-M6205AM
ZAVORE	Tektro [F]180mm, [R]160mm
ZAVORNE ROČICE	Tektro HD-J285
VERIŽNIK	Microshift Advent X G-Series 10-speed, 11x48
VERIGA	KMC X10 with missing link
GONILKE Z VERIŽNIKI	ProWheel Charm, 30t, 140mm
BOTTOM BRACKET	Press Fit

OBROČNIKI	
OBROČI	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology [F] 24" [R] 24"
PESTA	[F] Giant alloy, DBL, six-bolt [R] TRA HE, DBL, 72t pawl driver, 6 bolt
NAPERE	Sapim Laser
PLAŠČI	[F] Maxxis Minion DHF, 24x2.5, 60 TPI, folding, [R] Maxxis Minion DHR II, 24x2.4, 60 TPI, folding
DODATKI	Giant 1x chain guide

## GEOMETRIJA

OKVIR	One Size
Dolžina sedežne cevi (mm)	320
Kot sedežne cevi	77,0°
Top Tube Length (mm)	500
Višina glave okvirja (mm)	105
Krmilni kot	64,5°
Zamik vpetja osi (mm)	30
Trail (mm)	119,2
Medosna razdalja (mm)	1054,1
Dolžina cevi ob verigi (mm)	390
Bottom Bracket Drop (mm)	
Oddaljenost zgornje cevi od gonilne osi (mm)	534,6
Doseg (mm)	376,6
Višina zgornje cevi (mm)	641
Širina krmila (mm)	680
Dolžina opore krmila (mm)	40
Dolžina gonilke (mm)	140
Velikost obročnikov	24"

Vse navedene specifikacije se lahko spremenijo brez obvestila.