

FAITH 24



SPECIFIKACIJE

OKVIR	
VELIKOSTI	OSFM
BARVE	Cyber Lime
OKVIR	ALUXX SL-grade aluminum front and rear triangles, 130mm FlexPoint suspension, 24-inch rear wheel compatible
VILICE	Giant CREST TR, 140mm, FLOTUNE damper, 24-inch wheel compatible, custom "light weight" tune
AMORTIZER	Giant CREST FLOTRAC Lite, 165/45, trunnion mount, custom "light weight" tune
KOMPONENTE	
KRMILO	Giant Connect TR, alloy, 740mm, 20mm rise
GRIPS	Giant, custom small-hand sizing
OPORA KRMILA	Giant Contact, 8-degree, 40mm
OPORA SEDEŽA	Contact Switch AT Lite dropper, remote, 100mm travel, 30.9mm
SEDEŽ	Selle Royal Vivo Jr.
POGON	
PRESTAVNE ROČICE	MicroSHIFT Advent X, 1x10
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	MicroSHIFT Advent X
ZAVORE	Tektro HD-J2820, hydraulic, Tektro rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Tektro HD-J2820
VERIŽNIK	MicroSHIFT Advent X, G-Series, 11x48
VERIGA	KMC X10
GONILKE Z VERIŽNIKI	ProWheel CHARM, 30t, 140m
BOTTOM BRACKET	Press Fit

OBROČNIKI	
OBROČI	Giant TRA WheelSystem, aluminum, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology, [F] 24-inch, [R] 24-inch
PESTA	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), 6-bolt, MicroDrive driver body
NAPERE	Sapim, 28, straight pull, DBL Technology
PLAŠČI	[F] Maxxis Minion DHF, 24x2.4, 60 tpi [R] Maxxis Minion DHR II, 24x2.3, 60 tpi
DODATKI	Giant 1x chain guide

GEOMETRIJA

OKVIR	One Size
Dolžina sedežne cevi (mm)	320
Seat Post Insertion Depth (mm)	258
Kot sedežne cevi	77,0°
Top Tube Length (mm)	500
Višina glave okvirja (mm)	105
Krmilni kot	64,5°
Zamik vpetja osi (mm)	30
Trail (mm)	119,2
Medosna razdalja (mm)	1054
Dolžina cevi ob verigi (mm)	390
Bottom Bracket Drop (mm)	
Oddaljenost zgornje cevi od gonilne osi (mm)	535
Doseg (mm)	377
Višina zgornje cevi (mm)	641
Širina krmila (mm)	680
Dolžina opore krmila (mm)	40
Dolžina gonilke (mm)	140

Vse navedene specifikacije se lahko spremenijo brez obvestila.