



## 產品規格

車架	
顏色	Raw Aluminum
車架	ALUXX SL-Grade Aluminum front and rear triangles, 12x148mm thru-axle, 130mm FlexPoint suspension
前叉	Crest TR Elite Lite, FloTune Lite Damper, 140mm
避震器	Crest FloTrac Lite, 165/45mm, trunnion mount

COMPONENTS	
車把手	Giant Contact TR, 20mm rise, AL6061 aluminum, 680mm
把手帶/套	Giant small-hand
變桿	Giant Contact, 8 degrees, 40mm
座桿	Contact Switch AT Lite, 100mm
坐墊	Selle Royal Vivo Jr
踏板	Giant Pinner Lite

DRIVETRAIN	
變速把手	MicroSHIFT Advent X Trail trigger shifter SL-M9505-R (with nanowire)
前變速器	N/A
後變速器	Microshift Advent X RD-M6205AM
煞車系統	Tektro [F]180mm, [R]160mm
煞車把手	Tektro HD-J285
飛輪	Microshift Advent X G-Series 10-speed, 11x48
鍊條	KMC X10 with missing link
大齒盤	ProWheel Charm, 30t, 140mm
BOTTOM BRACKET (B B)	Press Fit

輪組	
輪圈	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology [F] 24" [R] 24"
花鼓	[F] Giant alloy, DBL, six-bolt [R] TRA HE, DBL, 72t pawl driver, 6 bolt
輻條	Sapim Laser
外胎	[F] Maxxis Minion DHF, 24x2.5, 60 TPI, folding, [R] Maxxis Minion DHR II, 24x2.4, 60 TPI, folding
其他	Giant 1x chain guide

Price: NT\$58,000

## 車架幾何

車架	One Size
座(立)管長 (mm)	320
座(立)管角度	77.0°
上管長度 (mm)	500
頭管長度 (mm)	105
頭管角度	64.5°
前叉 (mm)	30
Trail (mm)	119.2
前後輪距 (mm)	1054.1
後下叉長度 (mm)	390
五通下降高度 (mm)	
頭碗至五通高度 (mm)	534.6
頭碗至五通長度 (mm)	376.6
上管至地面高度 (mm)	641
把手寬 (mm)	680
龍頭長度 (mm)	40
曲柄長度 (mm)	140
輪組尺寸	24"

\* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。