



SPECIFIKACE

RÁM	
VELIKOSTI	jedna velikost (27,5" / 26" kola)
BARVA	Copper
RÁM	ALUXX SL-Grade Aluminum front and rear triangles, 12x148mm thru-axle, 135mm FlexPoint suspension
VIDLICE	Crest SL FloTune Lite, FloTune Lite Damper, 140mm
TLUMIČ	Crest FloTrac Lite, 165/45mm, trunnion mount
KOMPONENTY	
ŘÍDÍTKA	Giant Contact TR, 20mm rise, AL6061 aluminum,740mm
GRIPY	Giant small-hand
PŘEDSTAVEC	Giant Contact, 8 degree, 40mm
SEDLOVKA	Contact Switch AT Lite, 100mm
SEDLO	Giant Romero
PEDÁLY	Giant Pinner Lite
OSAZENÍ	
ŘAZENÍ	MicroSHIFT Advent X Trail trigger shifter SL-M9505-R (with nanowire)
PŘESMYKAČ	-
PŘEHAZOVAČKA	Microshift Advent X RD-M6205AM
BRZDY	Tektro [F]180mm, [R]160mm
BRZDOVÉ PÁKY	Tektro HD-J285
KAZETA	Microshift Advent X G-Series, 10-speed, 11x48
ŘETĚZ	KMC X10 with missing link
KLIKY	ProWheel Charm, 30t, 155mm
STŘED	Press Fit

KOLA	
RÁFKY	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology, [F] 27.5" [R] 26"
NÁBOJE	[F] Giant alloy, DBL, six-bolt [R] TRA HE, DBL, 72t pawl driver, 6 bolt
DRÁTY	Sapim Laser
PLÁŠTĚ	[F] Maxxis Minion DHF, 27.5x2.5, 60 TPI, folding, [R] Maxxis Minion DHR II, 26x2.4, 60 TPI, folding
DOPLŇKY	Giant 1x chain guide

Cena: 62 499 Kč

GEOMETRIE

RÁM	One Size
Délka sedlové trubky (mm)	350
Úhel sedlové trubky	77,0°
Délka horní trubky (mm)	545
Délka hlavové trubky (mm)	105
Úhel hlavové trubky	64,5°
Offset vidlice (mm)	41
Trail (mm)	126,5
Rozvor (mm)	1147,5
Délka řetězové vzpěry (mm)	425
Bottom Bracket Drop (mm)	10
Stack (mm)	584,5
Reach (mm)	410,1
Výška rámu od země (mm)	676
Šířka řídítek (mm)	740
Délka představce (mm)	40
Délka klik (mm)	155
Rozměr kol	F 27.5" / R 26"

Děláme vše pro to, aby veškeré údaje na tomto webu byly správné a aktuální. Přesto si ale musíme vyhradit právo na případné změny specifikací, barevného provedení a cen, a to bez předchozího upozornění. Děkujeme za pochopení.