



SPEZIFIKATIONEN

RAHMEN	
FARBE	Copper
RAHMEN	ALUXX SL-Grade Aluminum front and rear triangles, 12x148mm thru-axle, 135mm FlexPoint suspension
GABEL	Crest SL FloTune Lite, FloTune Lite Damper, 140mm
DÄMPFER	Crest FloTrac Lite, 165/45mm, trunion mount
KOMPONENTEN	
LENKER	Giant Contact TR, 20mm rise, AL6061 aluminum,740mm
GRIFFE	Giant small-hand
VORBAU	Giant Contact, 8 degree, 40mm
SATTELSTÜTZE	Contact Switch AT Lite, 100mm
SATTEL	Giant Romero
PEDALE	Giant Pinner Lite
ANTRIEB	
SCHALTHEBEL	MicroSHIFT Advent X Trail trigger shifter SL-M9505-R (with nanowire)
UMWERFER	N/A
SCHALTWERK	Microshift Advent X RD-M6205AM
BREMSEN	Tektro [F]180mm, [R]160mm
BREMSHEBEL	Tektro HD-J285
KASSETTE	Microshift Advent X G-Series, 10-speed, 11x48
KETTE	KMC X10 with missing link
KURBEL	ProWheel Charm, 30t, 155mm
TRETLAGER	Press Fit

LAUFRÄDER	
FELGEN	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology, [F] 27.5" [R] 26"
NABE	[F] Giant alloy, DBL, six-bolt [R] TRA HE, DBL, 72t pawl driver, 6 bolt
SPEICHEN	Sapim Laser
REIFEN	[F] Maxxis Minion DHF, 27.5x2.5, 60 TPI, folding, [R] Maxxis Minion DHR II, 26x2.4, 60 TPI, folding
EXTRAS	Giant 1x chain guide

GEOMETRIEDATEN

RAHMEN	One Size
Sitzrohrlänge (mm)	350
Sitzrohrwinkel	77.0°
Oberrohrlänge (mm)	545
Steuerrohr-Länge (mm)	105
Steuerrohr-Winkel	64.5°
Gabelneigung (mm)	41
Trail (mm)	126.5
Radstand (mm)	1147.5
Kettenstreben-Länge (mm)	425
Tretlager-Höhe (mm)	10
Stack (mm)	584.5
Reach (mm)	410.1
Überstandshöhe (mm)	676
Lenkerbreite (mm)	740
Vorbaulänge (mm)	40
Kurbellänge (mm)	155
Radgrösse	F 27.5" / R 26"

Spezifikations-, Preis- und Farbänderungen vorbehalten.