



SPECS

CADRU	
CULORI	Copper
CADRU	ALUXX SL-Grade Aluminum front and rear triangles, 12x148mm thru-axle, 135mm FlexPoint suspension
FURCA	Crest SL FloTune Lite, FloTune Lite Damper, 140mm
SOC	Crest FloTrac Lite, 165/45mm, trunion mount
COMPONENTE	
GHIDON	Giant Contact TR, 20mm rise, AL6061 aluminum,740mm
GRIPS	Giant small-hand
PIPA	Giant Contact, 8 degree, 40mm
TIJA SA	Contact Switch AT Lite, 100mm
SA	Giant Romero
PEDALE	Giant Pinner Lite
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	MicroSHIFT Advent X Trail trigger shifter SL-M9505-R (with nanowire)
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	Microshift Advent X RD-M6205AM
FRANE	Tektro [F]180mm, [R]160mm
MANETE FRANA	Tektro HD-J285
PINIOANE	Microshift Advent X G-Series, 10-speed, 11x48
LANT	KMC X10 with missing link
ANGRENAJ	ProWheel Charm, 30t, 155mm
BOTTOM BRACKET	Press Fit

ROTI	
JANTE	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology, [F] 27.5" [R] 26"
BUTUCI	[F] Giant alloy, DBL, six-bolt [R] TRA HE, DBL, 72t pawl driver, 6 bolt
SPITE	Sapim Laser
ANVELOPE	[F] Maxxis Minion DHF, 27.5x2.5, 60 TPI, folding, [R] Maxxis Minion DHR II, 26x2.4, 60 TPI, folding
EXTRAS	Giant 1x chain guide

GEOMETRIE

CADRU	One Size
Seat Tube Length (mm)	350
Seat Tube Angle	77,0°
Top Tube Length (mm)	545
Head Tube Length (mm)	105
Head Tube Angle	64,5°
Fork Rake (mm)	41
Trail (mm)	126,5
Wheelbase (mm)	1147,5
Chain Stay Length (mm)	425
Bottom Bracket Drop (mm)	10
Stack (mm)	584,5
Reach (mm)	410,1
Stand Over Height (mm)	676
Handlebar Width (mm)	740
Stem Length (mm)	40
Crank Length (mm)	155
Wheel Size	F 27.5" / R 26"

Toate specificatiile enumerate se pot schimba fara notificare prealabila.