



## SPECIFIKACIJE

OKVIR	
BARVE	Copper
OKVIR	ALUXX SL-Grade Aluminum front and rear triangles, 12x148mm thru-axle, 135mm FlexPoint suspension
VILICE	Crest SL FloTune Lite, FloTune Lite Damper, 140mm
AMORTIZER	Crest FloTrac Lite, 165/45mm, trunnion mount
KOMPONENTE	
KRMILO	Giant Contact TR, 20mm rise, AL6061 aluminum, 740mm
GRIPS	Giant small-hand
OPORA KRMILA	Giant Contact, 8 degree, 40mm
OPORA SEDEŽA	Contact Switch AT Lite, 100mm
SEDEŽ	Giant Romero
PEDALA	Giant Pinner Lite
POGON	
PRESTAVNE ROČICE	MicroSHIFT Advent X Trail trigger shifter SL-M9505-R (with nanowire)
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Microshift Advent X RD-M6205AM
ZAVORE	Tektro [F]180mm, [R]160mm
ZAVORNE ROČICE	Tektro HD-J285
VERIŽNIK	Microshift Advent X G-Series, 10-speed, 11x48
VERIGA	KMC X10 with missing link
GONILKE Z VERIŽNIKI	ProWheel Charm, 30t, 155mm
BOTTOM BRACKET	Press Fit

OBROČNIKI	
OBROČI	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology, [F] 27.5" [R] 26"
PESTA	[F] Giant alloy, DBL, six-bolt [R] TRA HE, DBL, 72t pawl driver, 6 bolt
NAPERE	Sapim Laser
PLAŠČI	[F] Maxxis Minion DHF, 27.5x2.5, 60 TPI, folding, [R] Maxxis Minion DHR II, 26x2.4, 60 TPI, folding
DODATKI	Giant 1x chain guide

## GEOMETRIJA

OKVIR	One Size
Dolžina sedežne cevi (mm)	350
Kot sedežne cevi	77,0°
Top Tube Length (mm)	545
Višina glave okvirja (mm)	105
Krmilni kot	64,5°
Zamik vpetja osi (mm)	41
Trail (mm)	126,5
Medosna razdalja (mm)	1147,5
Dolžina cevi ob verigi (mm)	425
Bottom Bracket Drop (mm)	10
Oddaljenost zgornje cevi od gonilne osi (mm)	584,5
Doseg (mm)	410,1
Višina zgornje cevi (mm)	676
Širina krmila (mm)	740
Dolžina opore krmila (mm)	40
Dolžina gonilke (mm)	155
Velikost obročnikov	F 27.5" / R 26"

Vse navedene specifikacije se lahko spremenijo brez obvestila.