



SPECIFIKACIJE

OKVIR	
VELIKOSTI	OSFM
BARVE	Obsidian Pulse
OKVIR	ALUXX SL-grade aluminum front and rear triangles, 135mm FlexPoint suspension, 26-inch rear wheel compatible
VILICE	Giant CREST SL, 140mm, FLOTUNE damper, 27.5-inch wheel compatible, custom "light weight" tune
AMORTIZER	Giant CREST FLOTRAC Lite, 165/45, trunnion mount, custom "light weight" tune
KOMPONENTE	
KRMILO	Giant Connect TR, alloy, 740mm, 20mm rise
GRIPS	Giant, custom small-hand sizing
OPORA KRMILA	Giant Contact, 8-degree, 40mm
OPORA SEDEŽA	Contact Switch AT Lite dropper, remote, 100mm travel, 30.9mm
SEDEŽ	Giant Romero
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	MicroSHIFT Advent X, 1x10
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	MicroSHIFT Advent X
ZAVORE	Tektro HD-J2820, hydraulic, Tektro rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Tektro HD-J2820
VERIŽNIK	MicroSHIFT Advent X, G-Series, 11x48
VERIGA	KMC X10
GONILKE Z VERIŽNIKI	ProWheel CHARM, 30t, 155m
BOTTOM BRACKET	Press Fit

OBROČNIKI	
OBROČI	Giant TRA WheelSystem, aluminum, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology, [F] 27.5-inch, [R] 26-inch
PESTA	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), 6-bolt, MicroDrive driver body
NAPERE	Sapim, 28, straight pull, DBL Technology
PLAŠČI	[F] Maxxis Minion DHF, 27.5x2.5, 60 tpi [R] Maxxis Minion DHR II, 26x2.4, 60 tpi
DODATKI	Giant 1x chain guide

GEOMETRIJA

OKVIR	One Size
Dolžina sedežne cevi (mm)	350
Seat Post Insertion Depth (mm)	285
Kot sedežne cevi	77,0°
Top Tube Length (mm)	545
Višina glave okvirja (mm)	105
Krmilni kot	64,5°
Zamik vpetja osi (mm)	41
Trail (mm)	123
Medosna razdalja (mm)	1148
Dolžina cevi ob verigi (mm)	425
Bottom Bracket Drop (mm)	10
Oddaljenost zgornje cevi od gonilne osi (mm)	585
Doseg (mm)	410
Višina zgornje cevi (mm)	676
Širina krmila (mm)	740
Dolžina opore krmila (mm)	40
Dolžina gonilke (mm)	155

Vse navedene specifikacije se lahko spremenijo brez obvestila.