

FASTROAD AR 1

GIANT



SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	Electron Blue
RAM	ALUXX-grade aluminum, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade composite, composite OverDrive steerer, 12x100mm thru-axle, disc
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Sport Flat, 31.8 XS:64cm, S:64cm, M:68cm, M/L: 68cm, L:68cm, XL:68cm
GREPPAR	Giant ErgoContact
STAM	Giant Contact, 8-degree XS:70mm, S:80mm, M:90mm, M/L:100mm, XL:110mm
SADELSTOLPE	Giant D-Fuse, alloy, 350mm
SADEL	Giant ErgoContact
PEDALER	platform pedal
DRIVLINA	
VÄXLAR	Shimano CUES U6000, 11-speed
FRAMVÄXEL	N/A
BAKVÄXEL	Shimano CUES
BROMSAR	Tektro HD-R280, Giant MPH rotors [F]160mm, [R]160mm
BROMSSPAKAR	Tektro HD-R280
KASSETT	Shimano CS-LG40011, 11x45
KEDJA	Shimano CN-LG500
VEVPARTI	FSA Omega AGX+, 42t XS:170mm, S:170mm, M:170mm, M/L:172.5mm, L:172.5mm, XL: 175mm
BROMSREGLAGE	threaded

HJUL	
FÄLGAR	Giant S-X2 Disc wheelset
NAV	Giant alloy, 12mm thru-axle
EKRAR	Sapim
DÄCK	Maxxis Re-Fuse, tubeless, 700x40c
EXTRAFUNKTIONER	tubeless prepared, 42mm max tire size
GRÄNSER	
MAX DÄCKAVSTÅND	42mm

Price: 16 990,00 kr

GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	455	475	495	525	555
Vinkel sadelrör	73,5°	73,5°	73,0°	73,0°	73,0°
Topprörets längd (mm)	560	575	590	610	630
Styrhuvud Längd (mm)	130	155	175	200	225
Vinkel styrhuvud	70,5°	71,0°	71,0°	71,5°	71,5°
Gaffelvinkel (mm)	50	50	50	50	50
Spår (mm)	73,7	70,4	70,4	67,1	67,1
Hjulbas (mm)	1047	1058	1069	1084	1105
Kedjestagslängd (mm)	435	435	435	435	435
Nedre fäste Drop (mm)	75	75	75	75	75
Stack (mm)	552	578	597	623	646
Reach (mm)	396	404	407	419	432
Stå över höjden (mm)	736	756	773	800	826
Styrets bredd (mm)	640	680	680	680	680
Stamlängd (mm)	80	90	90	100	110
Vevlängd (mm)	170	170	172,5	172,5	172,5
Hjulstorlek	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.