

# FASTROAD AR 2

**GIANT**



## SPECS

| FRAME            |   |
|------------------|---|
| SIZES            | XS, S, M, M/L, L, XL  |
| COLOURS          | Glacier Silver  |
| FRAME            | ALUXX-grade aluminum, 12x142mm thru-axle, disc                                    |
| FORK             | Advanced-grade composite, composite OverDrive steerer, 12x100mm thru-axle, disc   |
| SHOCK            | N/A   |
| COMPONENTS       |   |
| HANDLEBAR        | Giant Sport Flat, 31.8 XS:64cm, S:64cm, M:68cm, M/L: 68cm, L:68cm, XL:68cm        |
| GRIPS            | Giant ErgoContact   |
| STEM             | Giant Sports XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm               |
| SEATPOST         | Giant D-Fuse, alloy, 350mm  |
| SADDLE           | Giant ErgoContact   |
| PEDALS           | platform pedal  |
| DRIVETRAIN       |   |
| SHIFTERS         | Shimano CUES U4000, 9-speed   |
| FRONT DERAILLEUR | N/A   |
| REAR DERAILLEUR  | Shimano CUES  |
| BRAKES           | Tektro HD-R280, Giant MPH rotors [F]160mm, [R]160mm                               |
| BRAKE LEVERS     | Tektro HD-R280  |
| CASSETTE         | Shimano CS-LG3009, 11x41  |
| CHAIN            | Shimano CN-LG500  |
| CRANKSET         | FSA Omega AGX+, 42t XS:170mm, S:170mm, M:170mm, M/L:172.5mm, L:172.5mm, XL: 175mm |
| BOTTOM BRACKET   | threaded  |

| WHEELS             |                                       |
|--------------------|---------------------------------------|
| RIMS               | Giant S-X2 Disc wheelset              |
| HUBS               | Giant alloy, 12mm thru-axle           |
| SPOKES             | Sapim                                 |
| TYRES              | Maxxis Re-Fuse, tubeless, 700x40c     |
| EXTRAS             | tubeless prepared, 42mm max tire size |
| LIMITS             |                                       |
| MAX TIRE CLEARANCE | 42mm                                  |

**Price: €1,199.00**

## GEOMETRY

| FRAME                    | S     | M     | ML    | L     | XL    |
|--------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm)    | 455   | 475   | 495   | 525   | 555   |
| Seat Tube Angle          | 73.5° | 73.5° | 73.0° | 73.0° | 73.0° |
| Top Tube Length (mm)     | 560   | 575   | 590   | 610   | 630   |
| Head Tube Length (mm)    | 130   | 155   | 175   | 200   | 225   |
| Head Tube Angle          | 70.5° | 71.0° | 71.0° | 71.5° | 71.5° |
| Fork Rake (mm)           | 50    | 50    | 50    | 50    | 50    |
| Trail (mm)               | 73.7  | 70.4  | 70.4  | 67.1  | 67.1  |
| Wheelbase (mm)           | 1047  | 1058  | 1069  | 1084  | 1105  |
| Chain Stay Length (mm)   | 435   | 435   | 435   | 435   | 435   |
| Bottom Bracket Drop (mm) | 75    | 75    | 75    | 75    | 75    |
| Stack (mm)               | 552   | 578   | 597   | 623   | 646   |
| Reach (mm)               | 396   | 404   | 407   | 419   | 432   |
| Stand Over Height (mm)   | 736   | 756   | 773   | 800   | 826   |
| Handlebar Width (mm)     | 640   | 680   | 680   | 680   | 680   |
| Stem Length (mm)         | 80    | 90    | 90    | 100   | 110   |
| Crank Length (mm)        | 170   | 170   | 172.5 | 172.5 | 172.5 |
| Wheel Size               | 700C  | 700C  | 700C  | 700C  | 700C  |

All specifications listed are subject to change without notice.