

FASTROAD AR 2





SPECS

FRAME	
SIZES	XS, S, M, ML, L, XL
FRAME	ALUXX-Grade Aluminum 12x142mm thru-axle, Disc
FORK	Advanced-Grade Composite, Full Carbon, OverDrive Steerer 12x100mm thru-axle, Disc
COMPONENTS	
HANDLEBAR	Sport Flat, HL-MTB300BT, 0mm, 9 degree back sweep, 31.8 XS: 640, S: 640, M: 680, ML: 680, L: 680, XL: 680
GRIPS	ErgoContact D3
STEM	Giant Contact, 8 Degree XS: 70, S: 80, M: 90, ML: 90, L: 100, XL: 110
SEATPOST	Giant D-Fuse Alloy XS: 350, S: 350, M: 350, ML: 350, L: 350, XL: 350
SADDLE	GIANT ErgoContact Saddle
DRIVETRAIN	
SHIFTERS	Shimano Cues U4000 9 speed
REAR DERAILLEUR	Shimano Cues RD-U4000 9 Speed
BRAKES	Tektro HD-M3110, Giant Rotor, [F]160[R]160
BRAKE LEVERS	Tektro HD-M3110
CASSETTE	Shimano CSLG3009 11x41
CHAIN	KMC X11 with Missing Link
CRANKSET	FSA Omega AGX+, 42t XS: 170, S: 170, M: 170, ML: 172.5, L: 172.5, XL: 175
BOTTOM BRACKET	BB-4000

WHEELS	
RIMS	Giant S-X2 Disc 700C Wheelset, 12mm Thru Axles
TYRES	Maxxis Re-Fuse 60 tpi 700x40C, Wirebead, Tubless
EXTRAS	Tubeless Prepared
LIMITS	
MAX TIRE CLEARANCE	700x42C
MAX CHAINRING SIZE	Double 50/34 Single 42t

Price: €1,199.00

GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	455	475	495	525	555
Seat Tube Angle	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	560	575	590	610	630
Head Tube Length (mm)	130	155	175	200	225
Head Tube Angle	70.5°	71.0°	71.0°	71.5°	71.5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	73.7	70.4	70.4	67.1	67.1
Wheelbase (mm)	1047	1058	1069	1084	1105
Chain Stay Length (mm)	435	435	435	435	435
Bottom Bracket Drop (mm)	75	75	75	75	75
Stack (mm)	552	578	597	623	646
Reach (mm)	396	404	407	419	432
Stand Over Height (mm)	736	756	773	800	826
Handlebar Width (mm)	640	680	680	680	680
Stem Length (mm)	80	90	90	100	110
Crank Length (mm)	170	170	172.5	172.5	172.5

All specifications listed are subject to change without notice.