

FASTROAD AR ADVANCED 1

GIANT

SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Asphalt Green
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc
VILICE	Advanced-grade composite, composite OverDrive steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILLO	Giant Sport Flat, 31.8 XS:64cm, S:64cm, M:68cm, M/L: 68cm, L:68cm, XL:68cm
GRIPS	Giant ErgoContact
OPORA KRMILA	Giant Contact, 8-degree XS:70mm, S:80mm, M:90mm, M/L: 90mm, L:100mm, XL:110mm
OPORA SEDEŽA	Giant D-Fuse, composite, 350mm
SEDEŽ	Giant ErgoContact
PEDALA	platform pedal [GCS,GTS, GU, GV] N/A [all other GSC]
POGON	
PRESTAVNE ROČICE	SRAM Apex, 12-speed
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM Apex, 12-speed
ZAVORE	Shimano BR-U300, Giant MPH rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano BL-MT201
VERIŽNIK	SRAM Apex, 11x44
VERIGA	SRAM Apex D1
GONILKE Z VERIŽNIKI	SRAM Apex 1, 42t XS:170mm, S:170mm, M:170mm, M/L:172.5mm, L:172.5mm, XL: 175mm
BOTTOM BRACKET	FSA, press fit

OBROČNIKI	
OBROČI	Giant P-X2 Disc wheelset
PESTA	Giant alloy, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	Maxxis Re-Fuse, tubeless, 700x40c
DODATKI	tubeless prepared, 42mm max tire size
LIMITS	
MAX TIRE CLEARANCE	42mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	435	455	475	495	525	555
Kot sedežne cevi	73,5°	73,5°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	545	560	575	590	610	630
Višina glave okvirja (mm)	110	130	155	175	200	225
Krmilni kot	70,5°	70,5°	71,0°	71,0°	71,5°	71,5°
Zamik vpetja osi (mm)	50	50	50	50	50	50
Trail (mm)	73,7	73,7	70,4	70,4	67,1	67,1
Medosna razdalja (mm)	1031	1047	1058	1069	1084	1105
Dolžina cevi ob verigi (mm)	435	435	435	435	435	435
Bottom Bracket Drop (mm)	75	75	75	75	75	75
Oddaljenost zgornje cevi od gonilne osi (mm)	533	552	578	597	623	646
Doseg (mm)	387	396	404	407	419	432
Višina zgornje cevi (mm)	718	736	756	773	800	826
Širina krmila (mm)	640	640	680	680	680	680
Dolžina opore krmila (mm)	70	80	90	90	100	110
Dolžina gonilke (mm)	170	170	170	172,5	172,5	172,5
Velikost obročnikov	700C	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.