

FASTROAD AR ADVANCED 2



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Sport Flat
GRIPS	Giant ErgoContact
STEM	Giant Contact, 8-degree XS:70mm, S:80mm, M:90mm, M/L: 90mm, L:100mm, XL:110mm
SEATPOST	Giant D-Fuse, alloy, 350mm
SADDLE	GIANT ErgoContact Saddle
DRIVETRAIN	
SHIFTERS	Shimano Cues U6000 10 speed - SLU60010R
REAR DERAILLEUR	Shimano CUES
BRAKES	Tektro HD-M3110
BRAKE LEVERS	Tektro HD-M3110
CASSETTE	Shimano CSLG40010 11x48
CHAIN	KMC X11 with Missing Link
CRANKSET	FSA Omega AGX+, 42t
BOTTOM BRACKET	FSA BB-AL86

WHEELS	
RIMS	Giant S-X2 Disc, 12mm Thru Axles
TIRES	Giant Gavia Fondo 2, 60tpi 700X32C, Wirebead, Tubless
EXTRAS	Tubeless Prepared

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	435	455	475	495	525	555
Seat Tube Angle	73,5°	73,5°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	545	560	575	590	610	630
Head Tube Length (mm)	110	130	155	175	200	225
Head Tube Angle	70,5°	70,5°	71,0°	71,0°	71,5°	71,5°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	73,7	73,7	70,4	70,4	67,1	67,1
Wheelbase (mm)	1031	1047	1058	1069	1084	1105
Chain Stay Length (mm)	435	435	435	435	435	435
Bottom Bracket Drop (mm)	75	75	75	75	75	75
Stack (mm)	533	552	578	597	623	646
Reach (mm)	387	396	404	407	419	432
Stand Over Height (mm)	718	736	756	773	800	826
Handlebar Width (mm)	640	640	680	680	680	680
Stem Length (mm)	70	80	90	90	100	110
Crank Length (mm)	170	170	170	172,5	172,5	172,5

All specifications listed are subject to change without notice.