

FASTROAD AR ADVANCED 2



SPECS

| FRAME | |
|------------------|---|
| SIZES | XS, S, M, M/L, L, XL |
| COLOURS | Tiger Red |
| FRAME | Advanced-grade composite, 12x142mm thru-axle, disc |
| FORK | Advanced-grade composite, composite OverDrive steerer, 12x100mm thru-axle, disc |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Giant Sport Flat, 31.8 XS:64cm, S:64cm, M:68cm, M/L: 68cm, L:68cm, XL:68cm |
| GRIPS | Giant ErgoContact |
| STEM | Giant Contact, 8-degree XS:70mm, S:80mm, M:90mm, M/L: 90mm, L:100mm, XL:110mm |
| SEATPOST | Giant D-Fuse, alloy, 350mm |
| SADDLE | Giant ErgoContact |
| PEDALS | platform pedal [GCS,GTS, GU, GV] N/A [all other GSC] |
| DRIVETRAIN | |
| SHIFTERS | Shimano CUES U6000, 10-speed |
| FRONT DERAILLEUR | N/A |
| REAR DERAILLEUR | Shimano CUES |
| BRAKES | Tektro HD-R280, Giant MPH rotors [F]160mm, [R]160mm |
| BRAKE LEVERS | Tektro HD-R280 |
| CASSETTE | Shimano CS-LG40010, 11x48 |
| CHAIN | Shimano CN-LG500 |
| CRANKSET | FSA Omega AGX+, 42t XS:170mm, S:170mm, M:170mm, M/L:172.5mm, L:172.5mm, XL: 175mm |
| BOTTOM BRACKET | FSA, press fit |

| WHEELS | |
|--------------------|---------------------------------------|
| RIMS | Giant S-X2 Disc wheelset |
| HUBS | Giant alloy, 12mm thru-axle |
| SPOKES | Sapim |
| TIRES | Maxxis Re-Fuse, tubeless, 700x40c |
| EXTRAS | tubeless prepared, 42mm max tire size |
| LIMITS | |
| MAX TIRE CLEARANCE | 42mm |

Suggested Retail Price (CDN): \$2,249.00

FRAME GEOMETRY

| FRAME | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 455 | 475 | 495 | 525 | 555 |
| Seat Tube Angle | 73.5° | 73.5° | 73.0° | 73.0° | 73.0° |
| Top Tube Length (mm) | 560 | 575 | 590 | 610 | 630 |
| Head Tube Length (mm) | 130 | 155 | 175 | 200 | 225 |
| Head Tube Angle | 70.5° | 71.0° | 71.0° | 71.5° | 71.5° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | 50 |
| Trail (mm) | 73.7 | 70.4 | 70.4 | 67.1 | 67.1 |
| Wheelbase (mm) | 1047 | 1058 | 1069 | 1084 | 1105 |
| Chain Stay Length (mm) | 435 | 435 | 435 | 435 | 435 |
| Bottom Bracket Drop (mm) | 75 | 75 | 75 | 75 | 75 |
| Stack (mm) | 552 | 578 | 597 | 623 | 646 |
| Reach (mm) | 396 | 404 | 407 | 419 | 432 |
| Stand Over Height (mm) | 736 | 756 | 773 | 800 | 826 |
| Handlebar Width (mm) | 640 | 680 | 680 | 680 | 680 |
| Stem Length (mm) | 80 | 90 | 90 | 100 | 110 |
| Crank Length (mm) | 170 | 170 | 172.5 | 172.5 | 172.5 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C |

All prices and specifications are subject to change without notice.