

FASTROAD AR ADVANCED 2

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Tiger Red
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, composite OverDrive steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Sport Flat, 31.8 XS:64cm, S:64cm, M:68cm, M/L: 68cm, L:68cm, XL:68cm
GRIPS	Giant ErgoContact
STEM	Giant Contact, 8-degree XS:70mm, S:80mm, M:90mm, M/L: 90mm, L:100mm, XL:110mm
SEATPOST	Giant D-Fuse, alloy, 350mm
SADDLE	Giant ErgoContact
PEDALS	platform pedal [GCS,GTS, GU, GV] N/A [all other GSC]
DRIVETRAIN	
SHIFTERS	Shimano CUES U6000, 10-speed
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano CUES
BRAKES	Tektro HD-R280, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	Tektro HD-R280
CASSETTE	Shimano CS-LG40010, 11x48
CHAIN	Shimano CN-LG500
CRANKSET	FSA Omega AGX+, 42t XS:170mm, S:170mm, M:170mm, M/L:172.5mm, L:172.5mm, XL: 175mm
BOTTOM BRACKET	FSA, press fit

WHEELS	
RIMS	Giant S-X2 Disc wheelset
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Maxxis Re-Fuse, tubeless, 700x40c
EXTRAS	tubeless prepared, 42mm max tire size
LIMITS	
MAX TIRE CLEARANCE	42mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	435	455	475	495	525	555
Seat Tube Angle	73,5°	73,5°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	545	560	575	590	610	630
Head Tube Length (mm)	110	130	155	175	200	225
Head Tube Angle	70,5°	70,5°	71,0°	71,0°	71,5°	71,5°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	73,7	73,7	70,4	70,4	67,1	67,1
Wheelbase (mm)	1031	1047	1058	1069	1084	1105
Chain Stay Length (mm)	435	435	435	435	435	435
Bottom Bracket Drop (mm)	75	75	75	75	75	75
Stack (mm)	533	552	578	597	623	646
Reach (mm)	387	396	404	407	419	432
Stand Over Height (mm)	718	736	756	773	800	826
Handlebar Width (mm)	640	640	680	680	680	680
Stem Length (mm)	70	80	90	90	100	110
Crank Length (mm)	170	170	170	172,5	172,5	172,5
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.