

FASTROAD E+ EX D

GIANT



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDrive Pro, 80Nm, powered by Yamaha
TIPALO	RideControl Dash
PRIKAZOVALNIK	RideControl Dash
BATERIJA	EnergyPak Smart Compact 500WhEnergyPak Plus range extender compatible
OKVIR	
VELIKOSTI	XS, S, M, ML, L, XL
BARVE	Black
OKVIR	ALUXX Aluminum
VILICE	ALUXX SL-grade Aluminium, 12x100 thru-axle
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Connect XC Riser 31.8 x 690mm
GRIPS	Giant Contact Ergo
OPORA KRMILA	Giant Contact
OPORA SEDEŽA	Giant D-shape, Aluminium
SEDEŽ	Giant Sport
PEDALA	Aluminum Platform
POGON	
PRESTAVNE ROČICE	Shimano Tiagra
PREDNJI MENJALNIK	-
ZADNJI MENJALNIK	Shimano GRX RX400, 10-speed
ZAVORE	Shimano BR-MT200, hydraulic disc, 180/160mm
ZAVORNE ROČICE	Shimano BL-MT201
VERIŽNIK	Shimano Tiagra, 11-36, 10-speed
VERIGA	KMC e.10 Sport
GONILKE Z VERIŽNIKI	Forged Alloy minimal Q-factor, 42T
BOTTOM BRACKET	N/A

OBROČNIKI	
OBROČI	Giant eX-2, Tubeless Ready
PESTA	Giant Performance Tracker Road, Sealed Bearing
NAPERE	Sapim E-Lite [r] Race [f]
PLAŠČI	Kenda Kwick Seven.5 27.5 x 2.40 (61-584), 60TPI, w/ reflex
DODATNA OPREMA	
SVETILA	Axa BlueLine 50 frontAxa BlueLine rear
PRTLJAŽNIK	Giant Rack-It MIK

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	425	450	475	500	525	550
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	560	565	575	580	590	610
Višina glave okvirja (mm)	105	110	120	140	160	185
Krmilni kot	71,0°	71,0°	71,5°	71,5°	72,0°	72,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	74,5	74,5	71,2	71,2	67,9	67,9
Medosna razdalja (mm)	1070	1070	1071	1071	1076	1090
Dolžina cevi ob verigi (mm)	455	455	455	455	455	455
Bottom Bracket Drop (mm)	70	70	70	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	554	558	570	589	610	633
Doseg (mm)	407	405	406	400	404	410
Višina zgornje cevi (mm)	714	732	752	774	796	818
Širina krmila (mm)	690	690	690	690	690	690
Dolžina opore krmila (mm)	70	70	80	80	90	90
Dolžina gonilke (mm)	170	170	170	170	170	170
Velikost obročnikov	27.5"	27.5"	27.5"	27.5"	27.5"	27.5"

Vse navedene specifikacije se lahko spremenijo brez obvestila.