FATHOM E+ 1



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 3X 100Nm, PedalPlus 6-Sensor technology
STEUEREINHEIT	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
AKKU	Giant EnergyPak Smart 800Wh
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RAHMEN	
RAHMEN	ALUXX-grade aluminium, OverDrive, 148x12mm thru-axle, integrated KSA40 kickstand mount
GABEL	Giant STL 36 Air, 130mm travel, 5-position compression adjust, tapered steerer, 72mm crown, e-bike optimized, 110x15mm Boost axle, full fender compatible
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x760mm [S], 780mm [M-XXL]
GRIFFE	Giant Sole-O
VORBAU	Giant Contact SL
SATTELSTÜTZE	Giant Contact Switch AT dropper seatpost, 100mm travel
SATTEL	Giant Ergo Contact Trail
PEDALE	Anti-slip Platform
ANTRIEB	
SCHALTHEBEL	Shimano Cues
SCHALTWERK	Shimano Cues, LinkGlide 10-speed Shadow+
BREMSEN	Tektra Orion, hydraulic disc
BREMSHEBEL	Tektra Orion
KASSETTE	Shimano Cues11-48T 10-speed
KETTE	Shimano Cues, Linkglide CN-LG500
KURBEL	Forged alluminum direct-mount chainring steel 36T, Forged alumium crank arms

LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Shimano TC500, Boost, Center-Lock, 15x110mm[F] 12x148mm[R]
SPEICHEN	Stainless steel
REIFEN	Maxxis Rekon 29x2.4", EXO, 60TPI
ACCESSORIES	
SCHLOSS	ABUS Xplus battery lock

GEOMETRIEDATEN

RAHMEN	S	M	L	XL	XXL
Sitzrohrlänge (mm)	380	420	460	495	530
Sitzrohrwinkel	75.0°	75.0°	75.0°	75.0°	75.0°
Oberrohrlänge (mm)	590	610	630	650	670
Steuerrohr-Länge (mm)	110	120	130	140	150
Steuerrohr-Winkel	66.0°	66.0°	66.0°	66.0°	66.0°
Gabelneigung (mm)	51	51	51	51	51
Trail (mm)	113.5	113.5	113.5	113.5	113.5
Radstand (mm)	1197	1219	1241	1262	1284
Kettenstreben-Länge (mm)	470	470	470	470	470
Tretlager-Höhe (mm)	65	65	65	65	65
Stack (mm)	647	656	665	674	684
Reach (mm)	416	434	451	469	486
Überstandshöhe (mm)	730	757	750	773	776
Lenkerbreite (mm)	750	750	780	780	780
Vorbaulänge (mm)	50	50	50	50	50
Radgrösse	29"	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.