



СПЕЦИФИКАЦИИ

ХИБРИДНА ТЕХНОЛОГИЯ ЗА КОЛОЕЗДЕНЕ	
МОТОР	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
КОНТРОЛЕР	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
ДИСПЛЕЙ	Giant RideControl Dash, high-angle visibility, full color LCD display
БАТЕРИЯ	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
ЗАРЯДНО	Giant EnergyPak 4A smart charger compact, 60% charge in 3:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
РАМКА	
РАЗМЕР	S, M, L, XL, XXL
ЦВЯТ	Space Grey
РАМКА	ALUXX SL aluminum, Overdrive 1.5" - 1.8" head tube, 148x12mm thru-axle, integrated KSA40 kickstand mount, EnergyPak Plus range extender compatible
ВИЛКА	SR Suntour XCR 34 Boost 2-CR Air 29, 130mm travel, tapered 1.125"-1.5" steerer, 15AH2-110 thru-axle
КОМПОНЕНТИ	
КОРМИЛО	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
ГРИПОВЕ	Giant Tactal Pro, single lock-on
ЛАПА	Giant Contact
КОЛЧЕ ЗА СЕДАЛКА	Giant Contact Switch Adj, adjustable dropper, 30,9mm
СЕДАЛКА	Giant Ergo Contact Trail
ПЕДАЛИ	Aluminum Platform
DRIVETRAIN	
КОМАНДИ	Shimano Cues LinkGlide
ЗАДЕН ДЕРАЙЛЪОР	Shimano Cues LinkGlide, 11-speed
СПИРАЧКИ	Shimano Deore, BR-MT410, hydraulic disc, 180mm [F/R]
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano Deore
КАСЕТА	Shimano Cues LinkGlide, CL-LG400-11, 11-50T, 11-speed
ВЕРИГА	KMC eGlide NP/BK, e-bike optimized
КУРБЕЛ	FSA MegaTooth direct-mount 1X steel 36T FSA Comet E-Bike crank arm

КАПЛИ	
ШИНИ	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
ГЛАВИНИ	Giant eTracker Boost 15x110 [F] 12x148 [R]
СПИЦИ	Stainless Steel
ГУМИ	Maxxis Rekon 29x2.4" Wire Bead 60TPI
АКСЕСОАРИ	
СВЕТЛИНИ	Giant Recon E HL50 [F] Axa BlueLine Steady E6, 6-12V [R]
БАГАЖНИК	Giant Rack-It MIK

ГЕОМЕТРИЯ

РАМКА	S	M	L	XL	XXL
Seat Tube Length (mm)	380	420	460	495	530
Seat Post Insertion Depth (mm)	220	260	300	320	360
Seat Tube Angle	75,0°	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650	670
Head Tube Length (mm)	110	120	130	140	150
Head Tube Angle	66,0°	66,0°	66,0°	66,0°	66,0°
Fork Rake (mm)	51	51	51	51	51
Trail (mm)	113,4	113,4	113,4	113,4	113,4
Wheelbase (mm)	1197	1219	1241	1262	1284
Chain Stay Length (mm)	470	470	470	470	470
Bottom Bracket Drop (mm)	65	65	65	65	65
Stack (mm)	647	656	665	675	684
Обсер (mm)	416	434	451	469	486
Stand Over Height (mm)	730	757	750	773	776
Ширина на Кормило (mm)	750	780	780	780	780
Дължина на Лапа (mm)	40	40	50	50	50
Дължина на Курбел (mm)	165	165	165	165	165
Размер на Каплите	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

All specifications listed are subject to change without notice.