



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
DISPLAY	Giant RideControl Dash, high-angle visibility, full color LCD display
BATTERY	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 3:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	S, M, L, XL, XXL
ΧΡΩΜΑΤΑ	Space Grey
ΣΚΕΛΕΤΟΣ	ALUXX SL aluminum, Overdrive 1.5" - 1.8" head tube, 148x12mm thru-axle, integrated KSA40 kickstand mount, EnergyPak Plus range extender compatible
ΠΙΠΟΥΝΙ	SR Suntour XCR 34 Boost 2-CR Air 29, 130mm travel, tapered 1.125"-1.5" steerer, 15AH2-110 thru-axle

ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
GRIPS	Giant Tactal Pro, single lock-on
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact
ΛΑΙΜΟΣ ΣΕΛΛΑΣ	Giant Contact Switch Adj, adjustable dropper, 30,9mm
ΣΕΛΛΑ	Giant Ergo Contact Trail
ΠΕΝΤΑΛ	Aluminum Platform

ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Shimano Cues LinkGlide
ΝΤΕΡΑΓΓΙΕΡ ΟΠΤΙΣΘΙΟ.	Shimano Cues LinkGlide, 11-speed
ΦΡΕΝΑ	Shimano Deore, BR-MT410, hydraulic disc, 180mm [F/R]
ΜΑΝΥΕΤΤΕΣ ΦΡΕΝΩΝ	Shimano Deore
CASSETTE Ή ΕΛΕΥΘΕΡΟ	Shimano Cues LinkGlide, CL-LG400-11, 11-50T, 11-speed
ΑΛΥΣΙΔΑ	KMC eGlide NP/BK, e-bike optimized
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	FSA MegaTooth direct-mount 1X steel 36T FSA Comet E-Bike crank arm

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
ΚΕΝΤΡΑ	Giant eTracker Boost 15x110 [F] 12x148 [R]
ΑΚΤΙΝΕΣ	Stainless Steel
ΕΛΑΣΤΙΚΑ	Maxxis Rekon 29x2.4" Wire Bead 60TPI

ACCESSORIES	
LIGHTING	Giant Recon E HL50 [F] Axa BlueLine Steady E6, 6-12V [R]
CARRIER	Giant Rack-It MIK

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	S	M	L	XL	XXL
Seat Tube Length (mm)	380	420	460	495	530
Seat Post Insertion Depth (mm)	220	260	300	320	360
Seat Tube Angle	75,0°	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650	670
Head Tube Length (mm)	110	120	130	140	150
Head Tube Angle	66,0°	66,0°	66,0°	66,0°	66,0°
Fork Rake (mm)	51	51	51	51	51
Trail (mm)	113,4	113,4	113,4	113,4	113,4
Wheelbase (mm)	1197	1219	1241	1262	1284
Chain Stay Length (mm)	470	470	470	470	470
Bottom Bracket Drop (mm)	65	65	65	65	65
Stack (mm)	647	656	665	675	684
Reach (mm)	416	434	451	469	486
Stand Over Height (mm)	730	757	750	773	776
Handlebar Width (mm)	750	780	780	780	780
Stem Length (mm)	40	40	50	50	50
Crank Length (mm)	165	165	165	165	165
Wheel Size	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση