

FATHOM E+ 1 EX



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 3X, 100Nm, PedalPlus 6-Sensor technology
STEUEREINHEIT	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full color LCD display
AKKU	Giant EnergyPak, 800Wh
CHARGER	Giant EnergyPak 4A smart charger
RAHMEN	
RAHMEN	ALUXX-grade aluminium, OverDrive, 148x12mm thru-axle, integrated KSA40 kickstand mount
GABEL	Giant STL 36 Air, 130mm travel, 5-position compression adjust, tapered steerer, 72mm crown, e-bike optimized, 110x15mm Boost axle, full fender compatible
KOMPONENTEN	
LENKER	Giant Connect TR35, 20mm rise, 35x760mm [S], 35x780mm [M-XXL]
GRIFFE	Giant Sole-O
VORBAU	Giant Contact SL 35, 40 mm
SATTELSTÜTZE	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SATTEL	Giant Ergo Contact Trail
PEDALE	Large platform pedal, 28-pins, PP cage, steel axle
ANTRIEB	
SCHALTHEBEL	Shimano CUES, LinkGlide
SCHALTWERK	Shimano CUES, LinkGlide, 10-speed, Shadow+
BREMSEN	Tektro Orion, hydraulic disc, 4-piston, 203mm [F/R] rotors
BREMSHEBEL	Tektro Orion
KASSETTE	Shimano CUES, LinkGlide, 10-speed, 11x48
KETTE	Shimano LinkGlide
KURBEL	Forged aluminium, [XS/S] 165mm, [M/L] 170mm

LAUFRÄDER	
FELGEN	Giant XCT 29, tubeless ready, 25mm, e-bike optimized
NABE	Shimano TC500, Boost, Center-Lock, 15x110mm [F] 12x148mm [R]
SPEICHEN	Stainless steel
REIFEN	Maxxis Rekon, 29x2.4", wire bead, EXO, 60TPI
ACCESSORIES	
BELEUCHTUNG	Giant Recon EL50 Axa BlueLine Steady E6 rear
SCHLOSS	ABUS Xplus battery lock
GEPÄCKTRÄGER	MIK rack, system bag & basket compatibility
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	150kg

GEOMETRIEDATEN

RAHMEN	S	M	L	XL	XXL
Sitzrohrwinkel	75.0°	75.0°	75.0°	75.0°	75.0°
Oberrohrlänge (mm)	590	610	630	650	670
Steuerrohr-Länge (mm)	110	120	130	140	150
Steuerrohr-Winkel	66.0°	66.0°	66.0°	66.0°	66.0°
Radstand (mm)	1197	1219	1241	1262	1284
Kettenstreben-Länge (mm)	470	470	470	470	470
Stack (mm)	647	656	665	674	684
Reach (mm)	416	434	451	469	486
Kurbellänge (mm)	165	165	165	165	165

Spezifikations-, Preis- und Farbänderungen vorbehalten.