



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
PRIKAZ	Giant RideControl Dash, high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 3:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIČINE	S, M, L, XL, XXL
BOJE	Space Grey
OKVIR	ALUXX SL aluminum, Overdrive 1.5" - 1.8" head tube, 148x12mm thru-axle, integrated KSA40 kickstand mount, EnergyPak Plus range extender compatible
VILICA	SR Suntour XCR 34 Boost 2-CR Air 29, 130mm travel, tapered 1.125"-1.5" steerer, 15AH2-110 thru-axle
KOMPONENTE	
VOLAN	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
GRIPS	Giant Tactal Pro, single lock-on
LULA VOLANA	Giant Contact
CIJEV SJEDALA	Giant Contact Switch Adj, adjustable dropper, 30,9mm
SJEDALO	Giant Ergo Contact Trail
PEDALE	Aluminum Platform
POGON	
RUČICE MJENJAČA	Shimano Cues LinkGlide
STRAŽNJI MJENJAČ	Shimano Cues LinkGlide, 11-speed
KOČNICE	Shimano Deore, BR-MT410, hydraulic disc, 180mm [F/R]
RUČICE KOČNICA	Shimano Deore
KAZETA	Shimano Cues LinkGlide, CL-LG400-11, 11-50T, 11-speed
LANAC	KMC eGlide NP/BK, e-bike optimized
POGON	FSA MegaTooth direct-mount 1X steel 36T FSA Comet E-Bike crank arm

KOTAČI	
OBRUČI	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Giant eTracker Boost 15x110 [F] 12x148 [R]
ŽBICE	Stainless Steel
GUME	Maxxis Rekon 29x2.4" Wire Bead 60TPI
DODACI	
SVJETLA	Giant Recon E HL50 [F] Axa BlueLine Steady E6, 6-12V [R]
NOSAČ	Giant Rack-It MIK

GEOMETRIJA

OKVIR	S	M	L	XL	XXL
Dužina cijevi sjedala (mm)	380	420	460	495	530
Seat Post Insertion Depth (mm)	220	260	300	320	360
Kut cijevi sjedala	75,0°	75,0°	75,0°	75,0°	75,0°
Dužina gornje cijevi (mm)	590	610	630	650	670
Dužina prednje cijevi (mm)	110	120	130	140	150
Kut vilice	66,0°	66,0°	66,0°	66,0°	66,0°
Zakrivljenost vilice (offset) (mm)	51	51	51	51	51
Staza (mm)	113,4	113,4	113,4	113,4	113,4
Međuosovinski razmak kotača (mm)	1197	1219	1241	1262	1284
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	470	470	470	470	470
Položaj osovine pogona (mm)	65	65	65	65	65
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	647	656	665	675	684
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	416	434	451	469	487
Prekoračna visina (mm)	730	757	750	773	777
Širina volana (mm)	750	780	780	780	780
Dužina lule volana (mm)	40	40	50	50	50
Dužina poluge pedale (mm)	165	165	165	165	165
Veličina kotača	[F] 29" [R] 29"	[F] 29" [R] 29"	[F] 29" [R] 29"	[F] 29" [R] 29"	[F] 29" [R] 29"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.