



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
<b>SENSOR</b>	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
<b>DISPLAY</b>	Giant RideControl Dash, high-angle visibility, full color LCD display
<b>BATTERY</b>	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
<b>CHARGER</b>	Giant EnergyPak 4A smart charger compact, 60% charge in 3:00h
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRU	
<b>MARIMI</b>	S, M, L, XL, XXL
<b>CULORI</b>	Space Grey
<b>CADRU</b>	ALUXX SL aluminum, Overdrive 1.5" - 1.8" head tube, 148x12mm thru-axle, integrated KSA40 kickstand mount, EnergyPak Plus range extender compatible
<b>FURCA</b>	SR Suntour XCR 34 Boost 2-CR Air 29, 130mm travel, tapered 1.125"-1.5" steerer, 15AH2-110 thru-axle
COMPONENTE	
<b>GHIDON</b>	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
<b>GRIPS</b>	Giant Tactal Pro, single lock-on
<b>PIPA</b>	Giant Contact
<b>TIJA SA</b>	Giant Contact Switch Adj, adjustable dropper, 30,9mm
<b>SA</b>	Giant Ergo Contact Trail
<b>PEDALE</b>	Aluminum Platform
SISTEMUL DE SCHIMBARE A VITEZELOR	
<b>MANETE SCHIMBATOR</b>	Shimano Cues LinkGlide
<b>SCHIMBATOR SPATE</b>	Shimano Cues LinkGlide, 11-speed
<b>FRANE</b>	Shimano Deore, BR-MT410, hydraulic disc, 180mm [F/R]
<b>MANETE FRANA</b>	Shimano Deore
<b>PINIOANE</b>	Shimano Cues LinkGlide, CL-LG400-11, 11-50T, 11-speed
<b>LANT</b>	KMC eGlide NP/BK, e-bike optimized
<b>ANGRENAJ</b>	FSA MegaTooth direct-mount 1X steel 36T FSA Comet E-Bike crank arm

ROTI	
<b>JANTE</b>	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
<b>BUTUCI</b>	Giant eTracker Boost 15x110 [F] 12x148 [R]
<b>SPITE</b>	Stainless Steel
<b>ANVELOPE</b>	Maxxis Rekon 29x2.4" Wire Bead 60TPI
ACCESSORIES	
<b>LIGHTING</b>	Giant Recon E HL50 [F] Axa BlueLine Steady E6, 6-12V [R]
<b>CARRIER</b>	Giant Rack-It MIK

## GEOMETRIE

CADRU	S	M	L	XL	XXL
Seat Tube Length (mm)	380	420	460	495	530
Seat Post Insertion Depth (mm)	220	260	300	320	360
Seat Tube Angle	75,0°	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650	670
Head Tube Length (mm)	110	120	130	140	150
Head Tube Angle	66,0°	66,0°	66,0°	66,0°	66,0°
Fork Rake (mm)	51	51	51	51	51
Trail (mm)	113,4	113,4	113,4	113,4	113,4
Wheelbase (mm)	1197	1219	1241	1262	1284
Chain Stay Length (mm)	470	470	470	470	470
Bottom Bracket Drop (mm)	65	65	65	65	65
Stack (mm)	647	656	665	675	684
Reach (mm)	416	434	451	469	486
Stand Over Height (mm)	730	757	750	773	776
Handlebar Width (mm)	750	780	780	780	780
Stem Length (mm)	40	40	50	50	50
Crank Length (mm)	165	165	165	165	165
Wheel Size	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Toate specificatiile enumerate se pot schimba fara notificare prealabila.