

FATHOM E+ 1 EX

GIANT



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro 3X, 100Nm, PedalPlus 6-Sensor technology
TIPALO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
PRIKAZOVALNIK	Giant RideControl Dash 2, full color LCD display
BATERIJA	Giant EnergyPak, 800Wh
CHARGER	Giant EnergyPak 4A smart charger
OKVIR	
OKVIR	ALUXX-grade aluminium, OverDrive, 148x12mm thru-axle, integrated KSA40 kickstand mount
VILICE	Giant STL 36 Air, 130mm travel, 5-position compression adjust, tapered steerer, 72mm crown, e-bike optimized, 110x15mm Boost axle, full fender compatible
KOMPONENTE	
KRMILO	Giant Connect TR35, 20mm rise, 35x760mm [S], 35x780mm [M-XXL]
GRIPS	Giant Sole-O
OPORA KRMILO	Giant Contact SL 35, 40 mm
OPORA SEDEŽA	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SEDEŽ	Giant Ergo Contact Trail
PEDALA	Large platform pedal, 28-pins, PP cage, steel axle
POGON	
PRESTAVNE ROČICE	Shimano CUES, LinkGlide
ZADNJI MENJALNIK	Shimano CUES, LinkGlide, 10-speed, Shadow+
ZAVORE	Tektro Orion, hydraulic disc, 4-piston, 203mm [F/R] rotors
ZAVORNE ROČICE	Tektro Orion
VERIŽNIK	Shimano CUES, LinkGlide, 10-speed, 11x48
VERIGA	Shimano LinkGlide
GONILKE Z VERIŽNIKI	Forged aluminium, [XS/S] 165mm, [M/L] 170mm

OBROČNIKI	
OBROČI	Giant XCT 29, tubeless ready, 25mm, e-bike optimized
PESTA	Shimano TC500, Boost, Center-Lock, 15x110mm [F] 12x148mm [R]
NAPERE	Stainless steel
PLAŠČI	Maxxis Rekon, 29x2.4", wire bead, EXO, 60TPI
DODATNA OPREMA	
SVETILA	Giant Recon EL50 Axa BlueLine Steady E6 rear
KLJUČAVNICA	ABUS Xplus battery lock
PRTLJAŽNIK	MIK rack, system bag & basket compatibility
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	150kg

GEOMETRIJA

OKVIR	S	M	L	XL	XXL
Kot sedežne cevi	75,0°	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650	670
Višina glave okvirja (mm)	110	120	130	140	150
Krmilni kot	66,0°	66,0°	66,0°	66,0°	66,0°
Medosna razdalja (mm)	1197	1219	1241	1262	1284
Dolžina cevi ob verigi (mm)	470	470	470	470	470
Oddaljenost zgornje cevi od gonilne osi (mm)	647	656	665	674	684
Doseg (mm)	416	434	451	469	486
Dolžina gonilke (mm)	165	165	165	165	165

Vse navedene specifikacije se lahko spremenijo brez obvestila.