

FATHOM E+ 2

GIANT



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology
OHJAUSYKSIKKÖ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
NÄYTTÖ	Giant RideControl Dash, high-angle visibility, full color LCD display
AKKU	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 250 range extender compatible
LATURI	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
RUNKO	
KOOT	S, M, L, XL, XXL
VÄRIT	Gunmetal Black, Sun Beam
RUNKO	ALUXX SL aluminum, Overdrive 1.5" - 1.8" head tube, 148x12mm thru-axle, integrated KSA40 kickstand mount, EnergyPak Plus range extender compatible
HAARUKKA	SR Suntour XCR 34 Boost 2-CR Coil 29, 130mm travel, Tapered 1.125"-1.5" steerer, 15AH2-110 thru-axle
KOMONENTIT	
OHJAUSTANKO	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
GRIPIT	Giant Tactal Pro, single lock-on
OHJAINKANNATIN	Giant Contact
SATULATOLPPA	Giant Contact Switch Adj, adjustable dropper, 30,9mm
SATULA	Giant Ergo Contact Trail
POLKIMET	Aluminum Platform
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Cues LinkGlide
TAKAVAIHTAJA	Shimano Cues LinkGlide, 9-speed
JARRUT	Tektro HD-M285, hydraulic disc, 180mm [F/R]
JARRUKAHVAT	Tektro HD-M285
RATASPAKKA	Shimano Cues, LinkGlide, CS-LG300-9, 11-46T, 9-speed
KETJUT	KMC eGlide NP/BK, e-bike optimized
KAMPISARJA	FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36TChainline: 52mm, Max Chainring: 38T

RENKAAT	
VANTEET	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NAVAT	Giant eTracker Boost 15x110 [F] 12x148 [R]
PINNAT	Stainless steel
RENKAAT	Maxxis Rekon 29x2.4" Wire Bead 60TPI
TARVIKKEET	
VALOT	-
TAVARATELINE	-

Suositusuhinta: 3 729,00 €

GEOMETRIA

RUNKO	S
Satulaputken pituus (mm)	380
Satulatolpan asennussyvyys (mm)	220
Satulaputken kulma	75,0°
Vaakaputken pituus (mm)	590
Emäputken pituus (mm)	110
Emäputken kulma	66,0°
Haarukan offset (mm)	51
Trail-mitta (mm)	113,4
Akseliväli (mm)	1197
Takahaarukan alaputken pituus (mm)	470
Keskiön pudotus (mm)	65
Stack-mitta (mm)	647
Reach-mitta (mm)	416
Standover-mitta (mm)	730
Ohjaustangon leveys (mm)	750
Ohjainkannattimen pituus (mm)	40
Kammen pituus (mm)	165
Rengaskoko	[F] 29" [R]

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.