

FATHOM E+ 2

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology
SENSOR	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
DISPLAY	Giant RideControl Dash, high-angle visibility, full color LCD display
BATTERY	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CADRU	
MARIMI	S, M, L, XL, XXL
CULORI	Gunmetal Black, Sun Beam
CADRU	ALUXX SL aluminum, Overdrive 1.5" - 1.8" head tube, 148x12mm thru-axle, integrated KSA40 kickstand mount, EnergyPak Plus range extender compatible
FURCA	SR Suntour XCR 34 Boost 2-CR Coil 29, 130mm travel, Tapered 1.125"-1.5" steerer, 15AH2-110 thru-axle
COMPONENTE	
GHIDON	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
GRIPS	Giant Tactal Pro, single lock-on
PIPA	Giant Contact
TIJA SA	Giant Contact Switch Adj, adjustable dropper, 30,9mm
SA	Giant Ergo Contact Trail
PEDALE	Aluminium Platform
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano Cues LinkGlide
SCHIMBATOR SPATE	Shimano Cues LinkGlide, 9-speed
FRANE	Tektro HD-M285, hydraulic disc, 180mm [F/R]
MANETE FRANA	Tektro HD-M285
PINIOANE	Shimano Cues, LinkGlide, CS-LG300-9, 11-46T, 9-speed
LANT	KMC eGlide NP/BK, e-bike optimized
ANGRENAJ	FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36TChainline: 52mm, Max Chainring: 38T

ROTI	
JANTE	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
BUTUCI	Giant eTracker Boost 15x110 [F] 12x148 [R]
SPITE	Stainless steel
ANVELOPE	Maxxis Rekon 29x2.4" Wire Bead 60TPI
ACCESSORIES	
LIGHTING	-
CARRIER	-

GEOMETRIE

CADRU	S	M	L	XL	XXL
Seat Tube Length (mm)	380	420	460	495	530
Seat Post Insertion Depth (mm)	220	260	300	320	360
Seat Tube Angle	75,0°	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650	670
Head Tube Length (mm)	110	120	130	140	150
Head Tube Angle	66,0°	66,0°	66,0°	66,0°	66,0°
Fork Rake (mm)	51	51	51	51	51
Trail (mm)	113,4	113,4	113,4	113,4	113,4
Wheelbase (mm)	1197	1219	1241	1262	1284
Chain Stay Length (mm)	470	470	470	470	470
Bottom Bracket Drop (mm)	65	65	65	65	65
Stack (mm)	647	656	665	675	684
Reach (mm)	416	434	451	469	486
Stand Over Height (mm)	730	757	750	773	776
Handlebar Width (mm)	750	780	780	780	780
Stem Length (mm)	40	40	40	50	50
Crank Length (mm)	165	165	165	165	165
Wheel Size	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Toate specificatiile enumerate se pot schimba fara notificare prealabila.