

FATHOM E+ 2

GIANT



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology
TIPALO	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
PRIKAZOVALNIK	Giant RideControl Dash, high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
OKVIR	
VELIKOSTI	S, M, L, XL, XXL
BARVE	Gunmetal Black, Sun Beam
OKVIR	ALUXX SL aluminum, Overdrive 1.5" - 1.8" head tube, 148x12mm thru-axle, integrated KSA40 kickstand mount, EnergyPak Plus range extender compatible
VILICE	SR Suntour XCR 34 Boost 2-CR Coil 29, 130mm travel, Tapered 1.125"-1.5" steerer, 15AH2-110 thru-axle
KOMPONENTE	
KRMILO	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
GRIPS	Giant Tactal Pro, single lock-on
OPORA KRMILA	Giant Contact
OPORA SEDEŽA	Giant Contact Switch Adj, adjustable dropper, 30,9mm
SEDEŽ	Giant Ergo Contact Trail
PEDALA	Aluminum Platform
POGON	
PRESTAVNE ROČICE	Shimano Cues LinkGlide
ZADNJI MENJALNIK	Shimano Cues LinkGlide, 9-speed
ZAVORE	Tektro HD-M285, hydraulic disc, 180mm [F/R]
ZAVORNE ROČICE	Tektro HD-M285
VERIŽNIK	Shimano Cues, LinkGlide, CS-LG300-9, 11-46T, 9-speed
VERIGA	KMC eGlide NP/BK, e-bike optimized
GONILKE Z VERIŽNIKI	FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36TChainline: 52mm, Max Chainring: 38T

OBROČNIKI	
OBROČI	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
PESTA	Giant eTracker Boost 15x110 [F] 12x148 [R]
NAPERE	Stainless steel
PLAŠČI	Maxxis Rekon 29x2.4" Wire Bead 60TPI
DODATNA OPREMA	
SVETILA	-
PRTLJAŽNIK	-

GEOMETRIJA

OKVIR	S	M	L	XL	XXL
Dolžina sedežne cevi (mm)	380	420	460	495	530
Seat Post Insertion Depth (mm)	220	260	300	320	360
Kot sedežne cevi	75,0°	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650	670
Višina glave okvirja (mm)	110	120	130	140	150
Krmilni kot	66,0°	66,0°	66,0°	66,0°	66,0°
Zamik vpetja osi (mm)	51	51	51	51	51
Trail (mm)	113,4	113,4	113,4	113,4	113,4
Medosna razdalja (mm)	1197	1219	1241	1262	1284
Dolžina cevi ob verigi (mm)	470	470	470	470	470
Bottom Bracket Drop (mm)	65	65	65	65	65
Oddaljenost zgornje cevi od gonilne osi (mm)	647	656	665	675	684
Doseg (mm)	416	434	451	469	486
Višina zgornje cevi (mm)	730	757	750	773	776
Širina krmila (mm)	750	780	780	780	780
Dolžina opore krmila (mm)	40	40	40	50	50
Dolžina gonilke (mm)	165	165	165	165	165
Velikost obročnikov	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Vse navedene specifikacije se lahko spremenijo brez obvestila.