

FATHOM E+ 2

GIANT



SPECS

| HYBRID CYKELTEKNIK |                                                                                        |
|--------------------|----------------------------------------------------------------------------------------|
| MOTOR              | Giant SyncDrive Pro 3X, 100Nm, PedalPlus 6-Sensor technology                           |
| KONTROLLER         | Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels                |
| VISA               | Giant RideControl Dash 2, full color LCD display                                       |
| BATTERI            | Giant EnergyPak 625Wh                                                                  |
| LADDARE            | Giant EnergyPak 4A smart charger                                                       |
| RAM                |                                                                                        |
| RAM                | ALUXX-grade aluminium, OverDrive, 148x12mm thru-axle, integrated KSA40 kickstand mount |
| GAFFEL             | SR Suntour XCM34, 130mm travel, 15x110mm thru-axle                                     |
| KOMPONENTER        |                                                                                        |
| STYRE              | Giant Connect TR riser, 31.8x760mm [S], 31.8x780mm [M-XXL]                             |
| GREPPAR            | Giant Sole-O                                                                           |
| STAM               | Giant Contact                                                                          |
| SADELSTOLPE        | Forged Aluminium, 30.9mm, 2-bolt micro adjustable                                      |
| SADEL              | Giant Ergo Contact Trail                                                               |
| PEDALER            | Large platform pedal, 28-pins, PP cage, steel axle                                     |
| DRIVLINJA          |                                                                                        |
| VÄXLAR             | Shimano CUES, LinkGlide                                                                |
| BAKVÄXEL           | Shimano CUES, LinkGlide, 10-speed, Shadow+                                             |
| BROMSAR            | Shimano MT-200, hydraulic disc, 180mm [F/R] rotors                                     |
| BROMSSPAKAR        | Shimano MT-200                                                                         |
| KASSETT            | Shimano CUES, LinkGlide, 10-speed, 11x48                                               |
| KEDJA              | Shimano LinkGlide                                                                      |
| VEVPARTI           | Forged aluminium, [XS/S] 165mm, [M/L] 170mm                                            |

| HJUL                        |                                                              |
|-----------------------------|--------------------------------------------------------------|
| FÄLGAR                      | Giant XCT 29, tubeless ready, 25mm, e-bike optimized         |
| NAV                         | Shimano TC500, Boost, Center-Lock, 15x110mm [F] 12x148mm [R] |
| EKRAR                       | Stainless steel                                              |
| DÄCK                        | Maxxis Rekon, 29x2.4", wire bead, EXO, 60TPI                 |
| TILLBEHÖR                   |                                                              |
| LÅSA                        | ABUS Xplus battery lock                                      |
| GRÄNSER                     |                                                              |
| COMBINED MAXIMUM LOAD LIMIT | 150kg                                                        |

Price: 35 000,00 kr

GEOMETRY

| RAM                   | S     | M     | L     | XL    | XXL   |
|-----------------------|-------|-------|-------|-------|-------|
| Vinkel sadelrör       | 75,0° | 75,0° | 75,0° | 75,0° | 75,0° |
| Topprörets längd (mm) | 590   | 610   | 630   | 650   | 670   |
| Styrhuvud Längd (mm)  | 110   | 120   | 130   | 140   | 150   |
| Vinkel styrhuvud      | 66,0° | 66,0° | 66,0° | 66,0° | 66,0° |
| Hjulbas (mm)          | 1197  | 1219  | 1241  | 1262  | 1284  |
| Kedjestagslängd (mm)  | 470   | 470   | 470   | 470   | 470   |
| Stack (mm)            | 647   | 656   | 665   | 674   | 684   |
| Reach (mm)            | 416   | 434   | 451   | 469   | 486   |
| Vevlängd (mm)         | 165   | 165   | 165   | 165   | 165   |

All specifications listed are subject to change without notice.