

FATHOM E+ 3

GIANT



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport, 70Nm, PedalPlus 6-sensor technology
SENSOR	Giant RideControl Dash, Smart Assist automatic mode, 5 support levels, USB-C (10W)
PRIKAZ	Giant RideControl Dash, high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIČINE	S, M, L, XL, XXL
BOJE	Sangria
OKVIR	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, 141mm Boost QR, ISS, EnergyPak Plus Range Extender compatible, integrated KSA18 kickstand mount
VILICA	SR Suntour XCM32 NLO DS 15AH2 29, 120mm travel, tapered steerer, lockout
KOMPONENTE	
VOLAN	Giant Connect TR Riser 31.8 alloy 750mm [S], 780mm [M-XXL]
GRIPS	Giant Tactal single lock-on
LULA VOLANA	Giant Contact 31.8 alloy
CIJEV SJEDALA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SJEDALO	Giant Sport
PEDALE	Aluminium Platform
POGON	
RUČICE MJENJAČA	microSHIFT ADVENT e-optimized
STRAŽNJI MJENJAČ	microSHIFT ADVENT, 9-speed
KOČNICE	Tektro HD-M285, hydraulic disc, 180mm
RUČICE KOČNICA	Tektro HD-M285
KAZETA	microSHIFT ADVENT, 11-42T, 9-speed, e-optimized
LANAC	KMC e.9 Sport, e-bike optimized
POGON	FSA MegaTooth direct-mount 1X steel 36T alloy crank arm

KOTAČI	
OBRUČI	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Shimano HB-TC500-15 100x15 [F], MT200-B 141mm OLD QR [R]
ŽBICE	Stainless steel
GUME	Maxxis Rekon 29x2.4" Wire Bead 60TPI

GEOMETRIJA

OKVIR	S	M	L	XL	XXL
Dužina cijevi sjedala (mm)	380	420	460	495	530
Seat Post Insertion Depth (mm)	220	260	300	320	360
Kut cijevi sjedala	75,0°	75,0°	75,0°	75,0°	75°
Dužina gornje cijevi (mm)	590	610	630	650	670
Dužina prednje cijevi (mm)	110	120	130	140	150
Kut vilice	66,0°	66,0°	66,0°	66,0°	66°
Zakrivljenost vilice (offset) (mm)	51	51	51	51	51
Staza (mm)	113,4	113,4	113,4	113,4	111
Međuosovinski razmak kotača (mm)	1197	1219	1241	1262	1284
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	470	470	470	470	470
Položaj osovine pogona (mm)	65	65	65	65	65
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	647	656	665	675	684
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	416	434	451	469	487
Prekoračna visina (mm)	730	757	750	773	777
Širina volana (mm)	750	780	780	780	780
Dužina lule volana (mm)	40	40	50	50	50
Dužina poluge pedale (mm)	165	165	165	165	165
Veličina kotača	[F] 29" [R] [F] 29" [R] [F] 29" [R] [F] 29" [R] [F]				

Sve navedene specifikacije podložne su promjeni bez prethodne najave.