

FATHOM E+ 3

GIANT



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport, 70Nm, PedalPlus 6-sensor technology
TIPALO	Giant RideControl Dash, Smart Assist automatic mode, 5 support levels, USB-C (10W)
PRIKAZOVALNIK	Giant RideControl Dash, high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	S, M, L, XL, XXL
BARVE	Sangria
OKVIR	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, 141mm Boost QR, ISS, EnergyPak Plus Range Extender compatible, integrated KSA18 kickstand mount
VILICE	SR Suntour XCM32 NLO DS 15AH2 29, 120mm travel, tapered steerer, lockout
KOMPONENTE	
KRMILO	Giant Connect TR Riser 31.8 alloy 750mm [S], 780mm [M-XXL]
GRIPS	Giant Tactal single lock-on
OPORA KRMILA	Giant Contact 31.8 alloy
OPORA SEDEŽA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDEŽ	Giant Sport
PEDALA	Aluminum Platform
POGON	
PRESTAVNE ROČICE	microSHIFT ADVENT e-optimized
ZADNJI MENJALNIK	microSHIFT ADVENT, 9-speed
ZAVORE	Tektro HD-M285, hydraulic disc, 180mm
ZAVORNE ROČICE	Tektro HD-M285
VERIŽNIK	microSHIFT ADVENT, 11-42T, 9-speed, e-optimized
VERIGA	KMC e.9 Sport, e-bike optimized
GONILKE Z VERIŽNIKI	FSA MegaTooth direct-mount 1X steel 36T alloy crank arm

OBROČNIKI	
OBROČI	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
PESTA	Shimano HB-TC500-15 100x15 [F], MT200-B 141mm OLD QR [R]
NAPERE	Stainless steel
PLAŠČI	Maxxis Rekon 29x2.4" Wire Bead 60TPI

GEOMETRIJA

OKVIR	S	M	L	XL	XXL
Dolžina sedežne cevi (mm)	380	420	460	495	530
Seat Post Insertion Depth (mm)	220	260	300	320	360
Kot sedežne cevi	75,0°	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650	670
Višina glave okvirja (mm)	110	120	130	140	150
Krmilni kot	66,0°	66,0°	66,0°	66,0°	66,0°
Zamik vpetja osi (mm)	51	51	51	51	51
Trail (mm)	113,4	113,4	113,4	113,4	113,4
Medosna razdalja (mm)	1197	1219	1241	1262	1284
Dolžina cevi ob verigi (mm)	470	470	470	470	470
Bottom Bracket Drop (mm)	65	65	65	65	65
Oddaljenost zgornje cevi od gonilne osi (mm)	647	656	665	675	684
Doseg (mm)	416	434	451	469	486
Višina zgornje cevi (mm)	730	757	750	773	776
Širina krmila (mm)	750	780	780	780	780
Dolžina opore krmila (mm)	40	40	40	50	50
Dolžina gonilke (mm)	165	165	165	165	165
Velikost obročnikov	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Vse navedene specifikacije se lahko spremenijo brez obvestila.