

FATHOM E+



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 2 85Nm PedalPlus 6-Sensor technology
STEUEREINHEIT	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
AKKU	Giant EnergyPak Smart 750Wh
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RAHMEN	
GRÖSSEN	S, M, L, XL, XXL
FARBE	Deep Lake
RAHMEN	ALUXX aluminum, Overdrive 1.125" - 1.8" head tube, 148x12mm Thru-axle, integrated KSA40 kickstand mount
GABEL	SR Suntour XCR34 2CR coil boost 130mm travel 15x110mm AH axle
DÄMPFER	-
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
GRIFFE	Giant Sole-O
VORBAU	Giant Contact
SATTELSTÜTZE	Giant Contact Switch Core dropper seatpost, 100mm travel
SATTEL	Giant Ergo Contact Trail, ESG
PEDALE	Anti-slip Platform
ANTRIEB	
SCHALTHEBEL	Shimano Cues
SCHALTWERK	Shimano Cues 10-speed
BREMSSEN	Shimano MT200, hydraulic disc, 180mm [F/R]
BREMSHEBEL	Shimano BL-MT200
KASSETTE	Shimano Cues11-48T 10-speed
KETTE	Shimano Linkglide CN-LG500
KURBEL	Forged allumin direct-mount chainring steel 36T, Forged alumium crank arms

LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	eTracker boost alloy 6-bolt disc 15x110mm[F] 12x148mm[R]
SPEICHEN	Stainless steel
REIFEN	Maxxis Rekon 29x2.4", EXO, 60TPI
ACCESSORIES	
BELEUCHTUNG	-
SCHLOSS	ABUS Xplus battery lock
GEPÄCKTRÄGER	-

GEOMETRIEDATEN

RAHMEN	S	M	L	XL	XXL
Sitzrohrlänge (mm)	380	420	460	495	530
Sitzrohrwinkel	75.0°	75.0°	75.0°	75.0°	75.0°
Oberrohrlänge (mm)	590	610	630	650	670
Steuerrohr-Länge (mm)	110	120	130	140	150
Steuerrohr-Winkel	66.0°	66.0°	66.0°	66.0°	66.0°
Gabelneigung (mm)	51	51	51	51	51
Trail (mm)	113.5	113.5	113.5	113.5	113.5
Radstand (mm)	1197	1219	1241	1262	1284
Kettenstreben-Länge (mm)	470	470	470	470	470
Tretlager-Höhe (mm)	65	65	65	65	65
Stack (mm)	647	656	665	674	684
Reach (mm)	416	434	451	469	486
Überstandshöhe (mm)	730	757	750	773	776
Lenkerbreite (mm)	750	750	780	780	780
Vorbaulänge (mm)	50	50	50	50	50
Radgrösse	29"	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.