

# FATHOM E+

**GIANT**



## SPECS

HYBRID SYKKEL TEKNOLOGI	
MOTOR	Giant SyncDrive Pro 2 85Nm PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATTERI	Giant EnergyPak Smart 750Wh
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RAMME	
STØRRELSE	S, M, L, XL, XXL
FARGE	Deep Lake
RAMME	ALUXX aluminum, Overdrive 1.125" - 1.8" head tube, 148x12mm Thru-axle, integrated KSA40 kickstand mount
GAFFEL	SR Suntour XCR34 2CR coil boost 130mm travel 15x110mm AH axle
DEMPER	-
KOMPONENTER	
STYRE	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
GRIPS	Giant Sole-O
STYRSTEM	Giant Contact
SETEPINNE	Giant Contact Switch Core dropper seatpost, 100mm travel
SADEL	Giant Ergo Contact Trail, ESG
PEDALER	Anti-slip Platform
DRIVVERK	
GIRHENDLER	Shimano Cues
BAKGIR	Shimano Cues 10-speed
BREMSE	Shimano MT200, hydraulic disc, 180mm [F/R]
BREMSEHENDLER	Shimano BL-MT200
KASSETT	Shimano Cues11-48T 10-speed
KJEDE	Shimano Linkglide CN-LG500
KRANK	Forged aluminum direct-mount chainring steel 36T, Forged aluminum crank arms

HJUL	
FELG	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NAV	eTracker boost alloy 6-bolt disc 15x110mm[F] 12x148mm[R]
EIKE	Stainless steel
DEKK	Maxxis Rekon 29x2.4", EXO, 60TPI
TILBEHØR	
LYS	-
LÅS	ABUS Xplus battery lock
BAGASJEBRETT	-

## GEOMETRI

RAMME	S	M	L	XL	XXL
Seat Tube Length (mm)	380	420	460	495	530
Seat Tube Angle	75,0°	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650	670
Head Tube Length (mm)	110	120	130	140	150
Head Tube Angle	66,0°	66,0°	66,0°	66,0°	66,0°
Fork Rake (mm)	51	51	51	51	51
Wheelbase (mm)	1197	1219	1241	1262	1284
Chain Stay Length (mm)	470	470	470	470	470
Bottom Bracket Drop (mm)	65	65	65	65	65
Stack (mm)	647	656	665	674	684
Reach (mm)	416	434	451	469	486
Handlebar Width (mm)	750	780	780	780	780
Stem Length (mm)	40	40	50	50	50
Wheel Size	29"	29"	29"	29"	29"

Alle spesifikasjonene kan endres uten varsel.