

FATHOM E+



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro 2 85Nm PedalPlus 6-Sensor technology
TIPALO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
PRIKAZOVALNIK	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak Smart 750Wh
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	S, M, L, XL, XXL
BARVE	Deep Lake
OKVIR	ALUXX aluminum, Overdrive 1.125" - 1.8" head tube, 148x12mm Thru-axle, integrated KS-A40 kickstand mount
VILICE	SR Suntour XCR34 2CR coil boost 130mm travel 15x110mm AH axle
AMORTIZER	-
KOMPONENTE	
KRMILLO	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
GRIPS	Giant Sole-O
OPORA KRMILA	Giant Contact
OPORA SEDEŽA	Giant Contact Switch Core dropper seatpost, 100mm travel
SEDEŽ	Giant Ergo Contact Trail, ESG
PEDALA	Anti-slip Platform
POGON	
PRESTAVNE ROČICE	Shimano Cues
ZADNJI MENJALNIK	Shimano Cues 10-speed
ZAVORE	Shimano MT200, hydraulic disc, 180mm [F/R]
ZAVORNE ROČICE	Shimano BL-MT200
VERIŽNIK	Shimano Cues11-48T 10-speed
VERIGA	Shimano Linkglide CN-LG500
GONILKE Z VERIŽNIKI	Forged allumin direct-mount chainring steel 36T, Forged aluminum crank arms

OBROČNIKI	
OBROČI	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
PESTA	eTracker boost alloy 6-bolt disc 15x110mm[F] 12x148mm[R]
NAPERE	Stainless steel
PLAŠČI	Maxxis Rekon 29x2.4", EXO, 60TPI
DODATNA OPREMA	
SVETILA	-
KLJUČAVNICA	ABUS Xplus battery lock
PRTLJAŽNIK	-

GEOMETRIJA

OKVIR	S	M	L	XL	XXL
Dolžina sedežne cevi (mm)	380	420	460	495	530
Kot sedežne cevi	75,0°	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650	670
Višina glave okvirja (mm)	110	120	130	140	150
Krmilni kot	66,0°	66,0°	66,0°	66,0°	66,0°
Zamik vpetja osi (mm)	51	51	51	51	51
Trail (mm)	113,5	113,5	113,5	113,5	113,5
Medosna razdalja (mm)	1197	1219	1241	1262	1284
Dolžina cevi ob verigi (mm)	470	470	470	470	470
Bottom Bracket Drop (mm)	65	65	65	65	65
Oddaljenost zgornje cevi od gonilne osi (mm)	647	656	665	674	684
Doseg (mm)	416	434	451	469	486
Višina zgornje cevi (mm)	730	757	750	773	776
Širina krmila (mm)	750	750	780	780	780
Dolžina opore krmila (mm)	50	50	50	50	50
Velikost obročnikov	29"	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.