

FATHOM E+



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Pro 2 85Nm PedalPlus 6-Sensor technology
KONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
VISA	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATTERI	Giant EnergyPak Smart 750Wh
LADDARE	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RAM	
STORLEKAR	S, M, L, XL, XXL
FÄRGER	Deep Lake
RAM	ALUXX aluminum, Overdrive 1.125" - 1.8" head tube, 148x12mm Thru-axle, integrated KSA40 kickstand mount
GAFFEL	SR Suntour XCR34 2CR coil boost 130mm travel 15x110mm AH axle
BAKDÄMPARE	-
KOMPONENTER	
STYRE	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
GREPPAR	Giant Sole-O
STAM	Giant Contact
SADELSTOLPE	Giant Contact Switch Core dropper seatpost, 100mm travel
SADEL	Giant Ergo Contact Trail, ESG
PEDALER	Anti-slip Platform
DRIVLINA	
VÄXLAR	Shimano Cues
BAKVÄXEL	Shimano Cues 10-speed
BROMSAR	Shimano MT200, hydraulic disc, 180mm [F/R]
BROMSSPAKAR	Shimano BL-MT200
KASSETT	Shimano Cues11-48T 10-speed
KEDJA	Shimano Linkglide CN-LG500
VEVPARTI	Forged allumin direct-mount chainring steel 36T, Forged alumium crank arms

HJUL	
FÄLGAR	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NAV	eTracker boost alloy 6-bolt disc 15x110mm[F] 12x148mm[R]
EKRAR	Stainless steel
DÄCK	Maxxis Rekon 29x2.4", EXO, 60TPI
TILLBEHÖR	
BELYSNING	-
LÄSA	ABUS Xplus battery lock
BÄRARE	-

Price: 40 990,00 kr

GEOMETRY

RAM	S	M	L	XL
Längd sadelrör (mm)	380	420	460	495
Vinkel sadelrör	75,0°	75,0°	75,0°	75,0°
Topprörets längd (mm)	590	610	630	650
Styrhuvud Längd (mm)	110	120	130	140
Vinkel styrhuvud	66,0°	66,0°	66,0°	66,0°
Gaffelvinkel (mm)	51	51	51	51
Spår (mm)	113,5	113,5	113,5	113,5
Hjulbas (mm)	1197	1219	1241	1262
Kedjestagslängd (mm)	470	470	470	470
Nedre fäste Drop (mm)	65	65	65	65
Stack (mm)	647	656	665	674
Reach (mm)	416	434	451	469
Stå över höjden (mm)	730	757	750	773
Styrets bredd (mm)	750	750	780	780
Stamlängd (mm)	50	50	50	50
Hjulstorlek	29"	29"	29"	29"

All specifications listed are subject to change without notice.